LQ-2090IIN

DATASHEET / BROCHURE





Fast, networked 24-pin, 136-column dot matrix printer that offers outstanding reliability and an extremely low TCO.

The LQ-2090IIN is a high-volume dot matrix printer designed for fast and reliable printing. Upgrade your existing dot matrix printers to our latest model, which is now Energy Star compliant, and delivers built-in network capability with an incredibly low TCO.

Fast print speed

The LQ-2090IIN offers an improved USD (ultra speed draft) speed of 550 characters per second at 10 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

Increased reliability

Epson's dot matrix technology is already mature and very reliable. Building on this, the new printer improves the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

Same consumables

This printer uses the same ribbons as existing models, so you can upgrade your hardware and continue to use your current ribbon supplies.

Network capability

This is a network model which supports both serial and Ethernet connections for enhanced connectivity.

KEY FEATURES

- Fast print speed
 USD speed of 550 characters per second at 10 characters per inch
- Increased reliability
 Mean time between failure of 25,000
 power-on hours
- Increased number of copies Now original plus six copies
- Network capability
 Supports both serial and Ethernet connections
- Same consumables
 Uses the same ribbons as existing models



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method Impact dot matrix
Number of Pins 24 pins
Number of columns 136 columns
Pins 24 Pins

PRINT

Printing Speed Ultra Speed-Draft: 10 cpi: 550 chars/s

Barcodes Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E

Carbon Copies 6 plus one original

CONNECTIVITY

Interfaces Hi-Speed USB - compatible with USB 2.0 specification, Parallel, Ethernet interface (100 Base-

TX / 10 Base-T

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous paper front and rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels

(single- and multi-layer), Envelopes, Cardboard

Paper Thickness Continuous 0,12 mm - 0,46 mm

Paper

Paper Thickness Label Base 0.16 mm - 0.19 mm

Sheet

Paper Thickness Multi Part 0,12 mm - 0,46 mm Paper Thickness Single Sheet 0,065 mm - 0,14 mm

GENERAL

Energy Use 49 W

Product dimensions 612 x 375 x 177 mm (Width x Depth x Height)

Product weight 9,4 kg

Temperature Operation 5° C - 35° C Humidity Operation 10% - 80%

Compatible Operating Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows 8.1 x64 Edition,

Systems Windows Server 2003 x64, Windows Server 2016, Windows Vista, Windows Vista x64,

Windows XP, Windows XP Professional x64 Edition

Mean Time Between Failures 25.000 Hours

Print Head Life 400 Million Strokes/Wire Sound Pressure Operation: 55 dB (A) Noise Level Operation: 55 dB (A)

OTHER FEATURES

Input Data Buffer 128 kB

OTHER

Warranty 12 months Carry in

Optional warranty extension available

SUPPLIES

● Epson SIDM Black Ribbon Cartridge for LQ-2090 (C13S015336)

C13S015336

OPTIONAL ACCESSORIES

 Wide Pull Tractor Unit FX-2190II/LQ-2090II C12C933791

 Epson SIDM Push/pull tractor unit for FX-2190, LQ-2090 C12C800212

LOGISTICS INFORMATION

SKU	C11CF40402A0
EAN code	8715946651385
Country of Origin	Indonesia
Layer	2 Units

Epson Deutschland GmbH Otto-Hahn-Str. 4 D-40670 Meerbusch Info-Line: 02159 92 79 500 Telefax: +49 (0) 2159/538-3000 www.epson.de Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Bachteinhaber

Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

LQ-2090IIN

WHAT'S IN THE BOX

- User manual
- Driver and utilities (CD)
- Ribbon
- Power cable

