

# Product datasheet

Specifications



APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

SRTL2200RMXLI

## Overview

**Presentation** High density, double-conversion on-line power protection with scalable runtime.

**Lead time**

## Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	1980 W
<b>Rated power in VA</b>	2200 VA
<b>Input Connection Type</b>	IEC 60320 C20
<b>Output connection type</b>	6 IEC 60320 C13 2 IEC 60320 C19
<b>Number of rack unit</b>	3U
<b>Cable length</b>	1.83 m
<b>Number of cables</b>	1
<b>Battery type</b>	Li-Ion (Lithium-Ion)
<b>Provided equipment</b>	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

## General

<b>Product web sub-family</b>	Lithium-Ion
<b>Number of power module free slots</b>	0
<b>Number of power module filled slots</b>	0
<b>Redundant</b>	No

## Physical

Colour	Black with silver front bezel
Height	12.8 cm
Width	43.2 cm
Depth	63.9 cm
Net weight	30.5 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

## Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...275 V half load

## Output

Maximum configurable power in W	1980 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Built-in bypass
Maximum configurable power in VA	2200 VA

## Conformance

Product certifications	CE EAC
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA

Heat dissipation	317 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery voltage	48 V
Battery charger power	155 W rated
Battery power in VAh	605 VAh capacity 621 VAh runtime
Battery life	5...10 year(s)
Battery option	XBP48RM1U2-LI 1 1242 VAh XBP48RM1U2-LI 2 1863 VAh XBP48RM1U2-LI 3 2484 VAh XBP48RM1U2-LI 4 3105 VAh XBP48RM1U2-LI 5 3726 VAh XBP48RM1U2-LI 6 4347 VAh XBP48RM1U2-LI 7 4968 VAh XBP48RM1U2-LI 8 5589 VAh
Extended runtime	1

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	87 cm
Package 1 Length	60 cm
Package 1 Weight	41.4 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

# Contractual warranty

---

Warranty 5 year repair or replace

Recommended replacement(s)