

Product datasheet

Specifications



Power Cord, C20 to IEC309 (16A), 2.5m

AP9899

Overview

Presentation	This cable connects an IEC C19 outlet to an IEC 309-16A connector. It can be used as a means to plug in a 16A IEC 309 plug into a Rack PDU with IEC C19 outlets.
--------------	--

Lead time

Main

Input Connection Type	IEC 60320 C20
Cable length	2.50 m

Physical

Colour	Black
Height	9.5 cm
Width	29.2 cm
Depth	9.5 cm
Net weight	0.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Number of power socket outlets	1 IEC 60309 16 A 2P + E
--------------------------------	-------------------------

Conformance

Product certifications	VDE
------------------------	-----

Environmental

Ambient air temperature for operation	-10...40 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft

Ambient air temperature for storage	10...30 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	30.5 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.609 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	25.4 cm
Package 2 Width	32.2 cm
Package 2 Length	53.2 cm
Package 2 Weight	6.12 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	10
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	6.12 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------