Key **Features**

- · Advanced ergonomics with a 40° tilt, 130mm height adjustment, ±60°swivel, and ±90°pivot
- · Flexible connectivity with DisplayPort, HDMI, VGA, and USB 3.2
- TCO & Energy Star certificated
- · Versatile stand design for mounting a mini-PC or cloud client



Product **Description**

ViewSonic VG2748a-2 is a 27" Full HD monitor with productivity-enhancing features including IPS technology and an advanced ergonomic design for the modern-day office. Utilizing SuperClear® IPS panel technology and 1080P resolution, VG2748a-2 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customizable adjustments currently available to provide maximum comfort, including pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2748a-2 uses environmentally friendly packaging and offers a quick and easy out-of-the-box set-up via the quick release stand. The cloud client mounts on the back of the monitor stand coupled with cable management design features make VG2748a-2 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.2 inputs.



- 1. VESA Compatible(Wall Mount 100 x 100mm)

- 2. Menu Control Panel 3. USB 3.2 down stream x2 4. AC In
- 5. DisplayPort 6. HDMI
- 7. VGA 8. USB 3.2 up stream

DISPLAY		VIDEO INPUT	
Display Size (in.):	27	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Viewable Area (in.):	27		Separate/Composite/SOG - RGB
Panel Type:	IPS Technology	Analog Sync:	Analog
Resolution:	1920 x 1080	ERGONOMICS	
Resolution Type:	FHD (Full HD)	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	50M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	250 cd/m² (typ)	WEIGHT (IMPERIAL)	
Colors:	16.7M	Net (lbs):	15.5
Color Space Support:	8 bit (6 bit + A-FRC)	Net Without Stand (lbs):	10
Aspect Ratio:	16:9	Gross (lbs):	22.2
Response Time (Typical GTG):	5ms	WEIGHT (METRIC)	
Response Time (GTG w/OD):	5ms	Net (kg):	7
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (kg):	4.6
Backlight Life (Hours):	30000 Hrs (Min)	Gross (kg):	10.1
Curvature:	Flat	DIMENSIONS (IMPERIAL) (V	WXHXD)
		Packaging (in.):	27.2 x 16.9 x 8.6
Refresh Rate (Hz):	60 V	Physical (in.):	24.1 x 15.79~20.99 x 8
Blue Light Filter:	Yes	Physical Without Stand (in.):	24.1 x 14.2 x 2
Flicker-Free:	Yes	DIMENSIONS (METRIC) (WX	
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)	Packaging (mm):	692 x 430 x 218
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	Physical (mm):	612 x 401.19~533.24 x 202
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (mm):	612 x 362 x 52
COMPATIBILITY	Anti-Glare, Hard Goating (311)	. ,	012 X 302 X 32
PC Resolution (max):	1920x1080	GENERAL	aTIN/ua FCC B ICESONS Energy
, ,		Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC,
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 10/11 certified; macOS tested		UkrSEPRO, UKCA
Mac® Resolution (min):	1920x1080	PACKAGE CONTENTS:	VG2748A-2 x1, 3-pin Plug (IEC C13 CEE22) x1, DisplayPort Cable (v1.2;
CONNECTOR			Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
VGA:	1		Please dispose of in accordance with
USB 3.2 Type A Down Stream:	4	Recycle/Disposal:	local, state or federal laws.
USB 3.2 Type B Up Stream:	1	Warranty:	*Warranty offered may differ from
HDMI 1.4:	1		market to market
DisplayPort:	1	Power Management:	Energy Star standards, EPEAT
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO	· · · · · · · · · · · · · · · · · · ·		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	16.2W		
Eco Mode (optimized):	19.2W		
· · · /			
Consumption (typical):	23W		
Consumption (max):	25W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS	•		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL			
Frequency Horizontal:	24 ~ 82KHz		
Fraguenay Vertical:	50 7511		

Frequency Vertical:

50 ~ 75Hz