

Display Panel Size: Wide Screen 24.1"(61.13cm) 16:10

Color Saturation : 100%(sRGB)

Panel Type : IPS

True Resolution : 1920x1200

Display Viewing Area(HxV) : 518.4 x 324.0 mm

Display Surface : Non-glare

Pixel Pitch : 0.270mm

Brightness(Max) : 300 cd/m²

Contrast Ratio (Max) : 1000:1

ASUS Smart Contrast Ratio (ASCR) : 100000000:1

Viewing Angle (CR_{≥10}) : 178°(H)/178°(V)

Response Time : 5ms (Gray to Gray)

Display Colors : 16.7M

Flicker free

Video Feature Trace Free Technology : Yes

SPLendid Video Intelligence Technology

Skin-Tone Selection : 3 Modes

Color Temperature Selection : 4 Modes

QuickFit (modes) : Yes (Modes)

Low Blue Light : Yes

HDCP support : Yes

Audio Features Stereo Speakers : 2W x 2 Stereo RMS

I/O Ports Signal Input : HDMI, D-Sub, DisplayPort

PC Audio Input : 3.5mm Mini-Jack

Earphone jack : 3.5mm Mini-Jack

USB Port(s) : 3.0x4

Signal Frequency Analog Signal Frequency : 30 ~105 KHz (H) /49 ~75 Hz(V)

Digital Signal Frequency : 30 ~105 KHz (H) /49 ~75 Hz(V)

Power Consumption Power Consumption:<13.3W*

Power Saving Mode:<0.22W

Power Off Mode:0W(hard switch)

Voltage: 100~240V, 50 / 60 Hz

Mechanical Design Chassis Colors : Black

Tilt : -5°~+35°

Swivel : +90°~-90°

Pivot : +90°~-90°

Height Adjustment : 0~130 mm

VESA Wall Mounting : 100x100mm

Quick Release Stand Design : Yes

Security Kensington lock

Dimensions Phys. Dimension(with Stand)(WxHxD): 533 x505 x 211 mm

(highest),533 x 375 x 211 mm(lowest)

Phys. Dimension(without Stand ,For VESA Wall Mount)(WxHxD): 533 x 360 x 47 mm

Box Dimension (WxHxD): 649 x 474 x 192 mm

Weight6.1 Kg(Net with stand), 3.9 Kg(Net without stand);

8.3 Kg (Gross)

AccessoriesVGA cable

Audio cable

Power cord

DisplayPort cable
USB cable
Quick start guide
Warranty Card
MiniPC Kit

Compliance and Standards Energy Star®, BSMI, CB, CCC, CE, CEL level, CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, TUV-Ergo, TUV-GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8, Windows 7), RCM, TUV Flicker-free, KC, eStandby, TUV Low Blue Light, TCO, ICES-3, PC recycle

Note*measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection



• The actual transfer speed of USB 3.0, 3.1, 3.2, and/or Type-C will vary depending on many factors including the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment.

- Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products.
- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.