

Comfort² Line

Modern and elegant design

Fully pre-mounted for quick and easy installation

- Integrated cable channel
- Quick exchange of projector, e.g. for servicing
- 3D joint for tilting the projector ± 20° in all directions, rotates ± 180°
- · Can hold up to max. 20 kg
- Fixing points: 100 370 mm
- Crash protection in the interior of the telescopic tube
- Inner diameter: 37 mm
- Supplied with screws M3/M4/M5/M6 and height adjustable distance elements
- Stepless height adjustment
- NEW: supplied with plastic rosette, white (RAL 9003)



Details

 Integrated cable channel / Rosette



 Stepless height adjustment with safety stop



• Height adjustable distance elements



• 3D joint for tilting the projector in all directions up to ± 20°



· Quick exchange of projector



Kindermann Comfort² 60/100/150, stepless height-adjustable

Kindermann Comfort² Line - projector mount for the ceiling

and the second s			
Model	Distance projector / ceiling	Colour	Ref. No.
Kindermann Comfort ² 10	13 cm	metallic silver, RAL 9006	4000 000 010
		white, RAL 9003	4000 000 011
Kindermann Comfort ² 30	30 cm	metallic silver, RAL 9006	4000 000 030
		white, RAL 9003	4000 000 031
Kindermann Comfort ² 60	stepless from 45 up to 61 cm	metallic silver, RAL 9006	4000 000 060
		white, RAL 9003	4000 000 061
Kindermann Comfort ² 100	stepless from 65 up to 100 cm	metallic silver, RAL 9006	4000 000 100
		white, RAL 9003	4000 000 101
Kindermann Comfort ² 150	stepless from 105 up to 150 cm	metallic silver, RAL 9006	4000 000 150
		white, RAL 9003	4000 000 151