Rittal – The System.

Faster – better – everywhere.





ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

VerticalBox – DK 7501.000

created: 07.12.2020 on www.rittal.com/com-en



Product description	n
Description:	Compact 482.6 mm (19") enclosure for small networks.
Benefits:	May be used as wall-mounted, under-desk or desktop enclosure Free access from three sides for interior installation Passive ventilation with vent slots Rear panel prepared to accommodate a fan Freely selectable door hinging Space-saving, vertical mounting of 482.6 mm (19") installation components at the side
Material:	Sheet steel Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	RAL 7035
Supply includes:	Enclosure with glazed door Side panels (1 x fixed, 1 x slot-in) with vent slots Knockouts for cable entry via roof or base Slot-in rear panel with knockouts for cable entry and fan accommodation 482.6 mm (19") mounting level, 5 U, horizontal front and rear, depth-variable, distance between levels 434 – 489 mm Security lock 12321 on the door, side and rear panel 4 plastic feet, self-adhesive
Basic material:	Sheet steel
Product features	
Dimensions:	Width: 300 mm Height: 540 mm Depth: 600 mm

1

Installation height for components:	5 U
Packs of:	1 pc(s).
Weight/pack:	17.04 kg
EAN:	4028177625426
Customs tariff number:	94032080
ETIM 7.0:	EC002500
ETIM 6.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 6.0/6.1:	27180208
Product description:	DK VerticalBox, WHD: 300x550x600 mm, 5 U
Approvals	
Certificates:	EAC