

BOSTON BUSINESSLINE SERVER SERIES

FENWAY-22X312.4



PART NO: P3819



TECHNICAL SPECIFICATIONS

CHIPSET	Intel® SoC
SOCKET	Dual Socket E2 (LGA-4710) supports Intel® Xeon® 6500 & 6700 Processors
MEMORY	max. 4.0TB DDR5-6400 ECC registered
LAN	Dual Port 1000Base-T Network Adapter Broadcom BCM5720, 2x RJ45
GRAPHIC / AUDIO / GPU	ASPEED AST2600BMC, 1x VGA
SAS / SATA / NVMe	10x SATA 3.0 (6Gbs) Ports 8x NVMe PCI-E 5.0 x4 2x M.2 Port, PCI-E 5.0 x4, M-Key, Form Factor 2280, 22110
NO MAX. HDD/SSD	12x 2.5" / 3.5" Hot-swap NVMe / SAS / SATA drive bays
EXPANSION SLOTS	4x PCI-E 5.0 x16 Low Profile 2x PCI-E 5.0 x8 Low Profile
USB	6x USB 3.2 (4x rear + 2x internal headers)
INPUT / OUTPUT	2x COM Port (1x rear + 1x internal headers)
REMOTE / IPMI	IPMI 2.0, remote KVM console w/ virtual media, power control, health values, dedicated LAN
TPM	TPM 2.0 header
POWER SUPPLY	Redundant 1000W AC w/ PFC, 80 PLUS Titanium Level Certified

CONFIGURATION

(individual adaptations possible)

CHASSIS
2U Rackmount Server

DIMENSIONS (HxWxD)
89x437x647mm

POWER SUPPLY
Redundant 1000W AC w/ PFC, 80 PLUS Titanium Level Certified

MOTHERBOARD
Dual Socket E2 (LGA-4710)
supports Intel® Xeon® 6500 & 6700 Processors

CPU
2x Intel® Xeon® 6505P, 12-Cores,
2.20 GHz, HT, 48MB L3-Cache,
LGA-4710 E2B 2S, 150W (Granite Rapids SP)

MEMORY
16x 16GB (total 256GB) DDR5-6400, ECC registered

HARDWARE RAID
Optional

STORAGE DRIVES
1x 960GB TLC, SATA 6Gb/s, 2.5",
1 DWPD (read-intensive)

OPERATIONAL SYSTEM
Optional:
Microsoft® Windows™ Server
Red Hat Enterprise Standard Linux

SUPPORT SERVICES
36 month (Bring In)
Optional:
36 month onsite 9/5 NBD

DEUTSCHLAND

BOSTON Server & Storage Solutions GmbH
Kapellenstrasse 11 • 85622 Feldkirchen
T. +49 89 90901993 • sales@boston-it.de
www.boston-it.com/de

ÖSTERREICH

BOSTON Server & Storage Solutions GmbH
T. +43 660 2090400
E. sales@boston-it.at
www.boston-it.com/at

SCHWEIZ

BOSTON Server & Storage Solutions GmbH
Hafenstrasse 50C • 8280 Kreuzlingen
T. +41 71 5542275 • sales@boston-it.ch
www.boston-it.com/ch