## Key **Features**

- UWQHD for Incredible Visuals
- 1500R Curved Panel
- 100Hz Refresh rate delivers fluid visuals
- Dual 5W Speaker
- Integrated Docking Station with USB Type-C and Ethernet



## Product **Description**

The ViewSonic VG3456C is a 34" curved screen monitor with UWQHD 3440 x 1440 resolution and Eye ProTech technology, offering immersive visuals with enhanced eye comfort. Perfect for multi-tasking and productivity, it comes with built-in software, vDisplay Manager, to customise display arrangements and assign shortcuts via on-screen display control. With USB-C and Ethernet connectivity, this docking monitor serves as a complete hub for charging, data, network, and peripherals, reducing clutter and simplifying cable management. Additionally, you can tilt, swivel, and adjust the monitor's height to adapt to any setup or workflow, providing ergonomic flexibility.



Visit Us

6. USB 3.2 Downstream\*2

www.viewsonic.com



DISPLAY		CONTROLS	
Display Size (in.):	34	Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key
Viewable Area (in.):	34	,	5, Key 6 (power)
Panel Type:	VA Technology	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual
Resolution:	3440 x 1440	OPERATING CONDITIONS	Image Adjust, Setup Menu
Resolution Type:	UWQHD (UltraWide QHD)	Temperature:	32°E to 104°E (0°C to 40°C)
Static Contrast Ratio:	3,000:1 (typ)	Humidity (non-condensing):	32°F to 104°F (0°C to 40°C) 20% to 90%
Dynamic Contrast Ratio:	80M:1	WALL MOUNT	20 % 10 90 %
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	400 cd/m² (typ)	INPUT SIGNAL	700 X 100 IIIIII
Colors:	16.7M	Frequency Horizontal:	15 ~ 155KHz
Color Space Support:	8 bit (6 bit + FRC)	Frequency Vertical:	50 ~ 100Hz
Aspect Ratio:	21:9	VIDEO INPUT	
Response Time (Typical GTG):	5ms		TMDS - HDMI (v2.0), PCI-E -
Response Time (GTG w/OD):	5ms	Digital Sync:	DisplayPort (v1.2), Micro-Packet - Type C
Viewing Angles:	178º horizontal, 178º vertical	ERGONOMICS	<b>31</b>
Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	110
Curvature:	1500R	Swivel:	120°
Refresh Rate (Hz):	100	Tilt (Forward/Back):	-5° / 40°
Blue Light Filter:	Yes	WEIGHT (IMPERIAL)	
Flicker-Free:	Yes	Net (lbs):	20.1
Color Gamut:	NTSC: 72% size (Typ)	Net Without Stand (lbs):	14.8
Color Gamut:	sRGB: 104% size (Typ)	Gross (lbs):	32.4
Pixel Size:	0.232 mm (H) x 0.232 mm (V)	WEIGHT (METRIC)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net (kg):	9.1
COMPATIBILITY		Net Without Stand (kg):	6.7
PC Resolution (max):	3440x1440	Gross (kg):	14.7
Mac® Resolution (max):	3440x1440	DIMENSIONS (IMPERIAL) (WX	(HXD)
PC Operating System:	Windows 10/11 certified; macOS tested	Packaging (in.):	36.2 x 19 x 11
Mac® Resolution (min):	3440x1440	Physical (in.):	31.8 x 16.67~21 x 8.6
CONNECTOR		Physical Without Stand (in.):	31.8 x 15.3 x 4.6
USB 3.2 Type A Down Stream:	4	DIMENSIONS (METRIC) (WXH	XD)
USB 3.2 Type B Up Stream:	1	Packaging (mm):	920 x 482 x 280
USB 3.2 Type C Up Stream;	1 (98W power charger)	Physical (mm):	807 x 423.4~533.4 x 217
DisplayPort Alt mode :	i (9600 power charger)	Physical Without Stand (mm):	807 x 388 x 116
3.5mm Audio Out:	1	GENERAL	
HDMI 2.0:	2	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, RoHS, WEEE
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)	PACKAGE CONTENTS:	VG3456C x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male- Male) x1, USB Type-C Cable (Male- Male) x1, USB A/B Cable (v3.2; Male- Male) x1, Quick Start Guide x1
Ethernet LAN (RJ45):	1		
AUDIO			
Internal Speakers:	5Watts x2	Recycle/Disposal:	Please dispose of in accordance with
POWER	00.0014	Necycle/Disposal.	local, state or federal laws.
Eco Mode (Conserve):	32.29W	Warranty:	*Warranty offered may differ from market to market
Eco Mode (optimized):	35.21W	Power Management:	Energy Star standards, EPEAT
Consumption (typical):	38.53W		
Consumption (max):	46.72W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE	,		
Kensington Lock Slot:	1		
Cable Organization:	Yes		