# Product datasheet

Specifications



## Device monitoring and management, Network Management Cards, NMC3 for Easy UPS On-Line, secure remote UPS monitoring and management

AP9544

## Overview

**Presentation**

The Network Management Card for Easy UPS On-Line (AP9544) enables secure remote monitoring and control of one Easy UPS Online through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system.

A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card*. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates.

*The NMC Firmware must be V2.5 or later. Find the latest Firmware in the Software and Firmware section below.

**Lead time**

## Main

| | |
|---|---|
| **Range of product** | Network Management Cards |
| **Range compatibility** | Easy UPS On-Line<br>Easy UPS 1 Ph On-Line |
| **Product or component type** | Device monitoring and management |
| **Provided equipment** | Micro-USB cable<br>Installation manual |
| **Number of input phases** | 1 |
| **Standards** | CISPR 32<br>VCCI class A<br>ICES-003<br>EN 55024<br>EN 61000-4-2<br>EN 61000-4-3<br>EN 61000-4-4<br>EN 61000-4-5<br>EN 61000-4-6<br>EN 61000-4-8<br>EN 61000-6-2<br>EN/IEC 62040-2 |

## Physical

| | |
|---|---|
| **Product weight** | 0.05 kg |
| **Width** | 5.2 cm |
| **Height** | 4.4 cm |
| **Depth** | 8.0 cm |

## Conformance

Life Is On | Schneider Electric

| Product certifications | FCC Class A |
| --- | --- |
| | AS/NZS |
| | UK PSTI |

# Environmental

| Storage Relative Humidity | 0…95 % |
| --- | --- |
| Relative humidity | 0…95 % |
| Ambient air temperature for storage | -15…65 °C |
| ambient air temperature for operation | -5…45 °C |
| Storage altitude | 0.0000000000…15240.0000000000 m |
| Operating altitude | 0...10000 ft |

# Communications & Management

| Communication network type | 10/100/1000BASE-T |
| --- | --- |
| Authentication | Radius |
| communication port protocol | HTTP over secure sockets Layer (HTTPS) |
| | SSH |
| | FTP |
| | HTTP |
| | SNMP |
| | DHCP |
| | BOOTP (Bootstrap Protocol) |
| | TCP/IP |

# Packing Units

| Unit Type of Package 1 | PCE |
| --- | --- |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.600 cm |
| Package 1 Width | 16.500 cm |
| Package 1 Length | 23.000 cm |
| Package 1 Weight | 302.000 g |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 44 |
| Package 2 Height | 68.000 cm |
| Package 2 Width | 60.000 cm |
| Package 2 Length | 80.000 cm |
| Package 2 Weight | 21.000 kg |

# Logistical informations

| Country of origin | IE |
| --- | --- |

# Contractual warranty

| Warranty | 2 years repair or replace |
| --- | --- |

Life Is On | Schneider Electric

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ›

How we assess product sustainability ›

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | **69** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant with Exemptions** |
| SCIP Number | **F4c2965e-f80d-4830-8cd4-be926afb0f45** |
| REACh Regulation | **REACh Declaration** |
| China RoHS Regulation | **China RoHS declaration** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | **End of Life Information** |
| WEEE | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |
| Take-back | **No** |