



APC Power-Saving Back-UPS Pro 1200, 1200VA, 230V, 6 Schuko CEE 7 outlets (3 surge)

BR1200G-GR

V

Lead time

Main	
Main Input Voltage	230 V
Rated power in W	720 W
Rated power in VA	1200 VA
Nb of power socket outlets	3 Schuko CEE 7 3 Schuko CEE 7 surge
Cable length	1.52 m

General

Provided equipment	telephone cable user manual USB cable warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	30.1 cm
Width	11.2 cm
Depth	38.2 cm
Net weight	13 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency 50 Hz +/- 1 Hz 60 Hz +/- 1 Hz

Input voltage limits	156300 V adjustable 176294 V
Maximum input current	10 A
Switching current capacity	10 A

Output

Maximum configurable power in W	720 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Bypass type	Built-in bypass
Maximum configurable power in VA	1200 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Product certifications	BSI 1363 CE NEMKO
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m
Acoustic level	45 dBA

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Battery power in VAH	187 VAh runtime
Extended runtime	0

Surge Protection and Filtering

Surge energy rate	441 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line) RJ45 modem/fax/DSL protection (four wire dual line)

Packing Units

Package 1 Weight	13.8 kg
Package 1 Height	39 cm
Package 1 width	23.5 cm
Package 1 Length	49 cm
SCC14	10731304286834

Offer Sustainability

Green Premium product
REACh Declaration
Compliant EU RoHS Declaration
Yes
Yes
Product Environmental Profile
End of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Energy efficient product
Take-back program available

Contractual warranty

Warranty 2 years repair or replace, 3 years repair or replace for European Union countries		
	Warranty	2 years repair or replace, 3 years repair or replace for European Union countries