

# Rittal – The System.

Faster – better – everywhere.

## **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.735**

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.735

created: 07.12.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Design:</b>	Pre-configured
<b>Description:</b>	Wall-mounted enclosure with optimum accessibility due to hinged part.
<b>Material:</b>	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Powder-coated
<b>Colour:</b>	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
<b>Protection category IP to IEC 60 529:</b>	IP 54 in conjunction with solid gland plate, top and bottom
<b>IK Code:</b>	IK08
<b>Supply includes:</b>	Wall section with solid gland plate at the top and brush strip at the bottom, two vertical mounting rails and C rail, horizontal, for cable clamping Hinged part with 25 mm pitch pattern of holes in the front and rear frame, two 482.6 mm (19") mounting angles at the front, infinitely depth-variable, and side outlet filters on the left and right Earth rail with star earthing Designer glazed door 1 double-kit key no. 5 Wall mounting bracket, 10 mm Mini-comfort handle for lock inserts Security lock 3524 E
<b>Basic material:</b>	Sheet steel

## Product features

<b>Dimensions:</b>	Width: 600 mm Height: 746 mm Units: 15 U Depth: 573 mm
<b>Depth hinged part:</b>	416 mm
<b>Installation depth:</b>	520 mm
<b>Clearances:</b>	Clearance width: 502 mm Clearance height: 683 mm
<b>Wall section:</b>	Depth: 135 mm
<b>Load capacity:</b>	Hinged part, static (max.): 750 N
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	45 kg
<b>EAN:</b>	4028177324244
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC000261
<b>ETIM 6.0:</b>	EC000261
<b>eCl@ss 8.0/8.1:</b>	27142408
<b>eCl@ss 6.0/6.1:</b>	27180208
<b>Product description:</b>	DK Wall-mounted enclosures, 3-part, WHD: 600x746x573 mm, 15 U, Pre-configured, with mounting angles, depth-variable

## Approvals

<b>Approvals:</b>	UL + C-UL
<b>Certificates:</b>	EAC IK-Code Protection category
<b>Declarations:</b>	Declaration of conformity