
Fujitsu recommends Windows 10 Pro for business.



Data Sheet FUJITSU Desktop ESPRIMO G5010

Mini, Mighty | Takes up your challenges, not your space

The FUJITSU ESPRIMO G5010 is a stylish mini PC which offers desktop functionality in an ultra-compact, space-saving design. Latest Intel chipset and 10th Gen Intel® Core™ processors provides the performance for daily office needs. It supports flexible mounting options – attach to displays, wall mount, under table mount. Its compact size and wide range of interfaces make it an ideal where space saving is critical for the business.



Small footprint; energy and space-saving device for clean, clutter-free desk

- Fully equipped PC with a volume of only ~0.86 liters
- Impressive performance/volume ratio and is easy to set up in minutes

Ultimate usability

Flexible mounting options and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls

Small yet grand

High performance in a small mini PC design

- Latest Intel chipset technology and 10th generation Intel® Core™ processor family
- Legacy support for standard mini PC interfaces- DisplayPort, HDMI, USB Type-A

Perfect fit for modern offices and workplaces of tomorrow

The PC which can transform your workplace for the next generation

- Supports new workplace scenarios with a single Type-C connection
- Type-C Docking port for future workplace and AiO-like usage

Feature-rich and energy-efficient

Do a lot more with this mini-PC and also get lesser energy bill

- Improved energy efficiency
- Next generation INTEL integrated graphics
- Type-C connector with convenient front access to support modern peripherals like Type-C USB sticks or headsets











Components

Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annua Channel Support" at http://support.ts.fujitsu.com.
Processor	Intel® Core™ i7-10700T processor (8 Cores / 16 Threads, 2.00 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i5-10600T processor (6 Cores / 12 Threads, 2.40 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10500T processor (6 Cores / 12 Threads, 2.30 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10400T processor (6 Cores / 12 Threads, 2.00 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i3-10100 processor (4 Cores / 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) *
	Intel® Celeron® processor G5905 (2 Cores / 2 Threads, 3.50 GHz, 4 MB, Intel® UHD Graphics 610)
	Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610)
	*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and othe variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)
Ethernet (RJ-45)1	
Memory modules	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
Mass storage 2.5 inch size	HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch
	HDD SATA III, 5,400 rpm, 1000 GB, 2.5-inch
	HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height
Interface add on cards/components (optional)	
(οραστιαι)	Intel® WI-FL6 AX200 and Bluetooth 5.1. SRD 5.8GHz (dedicated regions only)

Intel® WI-FI 6 AX200 and Bluetooth 5.1, SRD 5.8GHz (dedicated regions only)

Base unit

D '1	ECDDIMO CEO10	
Base unit	ESPRIMO G5010	

Mainboard	
Mainboard type	D3804
Formfactor	proprietary
Chipset	Intel® H410
Processor socket	LGA 1200
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Realtek RTL8111H
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Audio features	Internal speaker supports audio playback (optional), High Definition audio
I/O controller on board	
Serial ATA total	1
thereof SATA III	1
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Front audio: headset	1
USB 2.0 total	3
USB 3.2 Gen 1 (5 Gbps) total	4
USB front	1x Type-A USB 3.2 Gen 1; 1x Type-C USB 2.0 (supports up to 15W)
USB rear	2x Type-A USB 2.0; 2x Type-A USB 3.2 Gen 1; 1x Type-C USB 3.2 Gen 1, supports DisplayPort 1.4 and power delivery e.g. from a display)
VGA	optional: via external active adapter cable
DisplayPort	1
HDMI	1
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality, Optional Type-C port supports DisplayPort 1.4 and Power Delivery (PD) e.g. from Display, HDMI Ver. 1.4
Kensington Lock support	1
Input device / components	
Input devices (optional)	Keyboard Mouse
Drive bays	
Drive bays total	1
2.5-inch internal bays	' 1
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s)
	. A G. Hamilbourd for SSD fitting (r Cic S.0 AT, up to SZGDig 3)
Mini PCI slots	an are the could for MILAN are also be
M.2-2230	on mainboard for WLAN module
Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630

Graphics on board	
Shared video memory	Up to half size of total system memory
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30 Hz)
Graphics features	Dual display support DirectX® 12
	HDCP support
	OpenCL [™] 2.1
	OpenGL® 4.5
	DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels)
	USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use)
•	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
	For TF1 we recommend using ours
Electrical values	I ((:
Power efficiency note	power supply efficiency at 115/230V: 89% average efficiency
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range Operating line frequency range	90 V - 264 V 47 Hz - 63 Hz
	65 W
Max. output of single power supply	05 W
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	https://docs.ts.fujitsu.com/dl.aspx?id=5a01a770-86f9-4fb4-b05c-0c9ae0597391
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processors for noise	Intel® Core™ i5-10500T processor and
	8GB, no ODD, Windows 10 (tower position)
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.1 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
Standard noise operation mode: HDD	3.4 B / 22 dB(A) Bystander; 24 dB(A) Operator position (SSD M.2)
load	
Standard noise operation mode: Idle	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
mode	
Standard noise operation mode: Office	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
applications 2.0	
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	146.9 x 164.5 x 36 mm
	5.78 x 6.48 x 1.42 inch
Operating position	horizontal / vertical (optional, feet needed)
VESA mount	optional mounting kit
Weight	0.8 kg
Weight (lbs)	1.76 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)
Compliance	
Product	ESPRIMO G5010

Compliance		
Model	TCS5	
Germany	GS	
Europe	CE	
USA/Canada	FCC Class B cTUVus	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 TCO Certified 8.0 (depending on configuration) EPEAT® Silver (dedicated regions), depending on configuration	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)	
Manageability		
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	
Manageability software	DeskView Client DeskView Instant BIOS Management	
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management	
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Security		
Physical Security	Kensington Lock support	
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCle NVME) Modern Standby ready (for configurations with NVMe SSD and w/o PCle cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) AuthConductor Client Basic (secure authentication solution)	

Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required)
	Keyboard on with one key (KBPX Eco, KB521)
	Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards
	Keyboard on with any key (USB) Thermal management
	Extended lifetime
Accessories information	Further helpful options
	Desktop Accessories:
	http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/
	http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/
	Stands and Mounting kits:
	http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Packaging information	
Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	If keyboard is inlcuded in packaging: 1.) packaging dimension is increasing to: $500 \times 208 \times 290 \text{mm} / (19.69 \times 8.19 \times 11.42 \text{ inch})$; 2.) material weight of carton will increase to $880g$; 3.) max. quantity/pallet = 56 ; printed user documentation is bleached in chlorin free process;
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions Product Support Services - the perfect	http://www.fujitsu.com/warranty extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
	_
Spare Parts availability	5 years

Recommended Accessories

DisplayPort to DisplayPort 1.4 Cable



The Fujitsu DisplayPort to DisplayPort Cable connects your system with your display offering you an ultra high resolution graphics connection up to (8K UHD (7.680×4.320 Pixel) @ 60 Hz).

Order Code: \$26391-F6055-L219

HDMI to HDMI Cable



The Fujitsu HDMI to HDMI Cable connects your display with your system or Order Code:

Port Replicator. S26391-F6055-L230

USB Type-C to USB Type-A Adapter



The FUJITSU USB Type-C to USB Type-A Adapter allows you to connect Accessories with an USB Type-A interface with your system.

Order Code: \$26391-F6058-L100 USB-C Cable 5A Gen2



The FUJITSU USB-C Cable 5A Gen2 allows you to connect Accessories with Order Code: an USB Type-C interface with your system.

S26391-F6058-L101

USB-C to HDMI2.0 Adapter



The FUJITSU USB-C to HDMI2.0 Adapter enables the connection of HDMI displays to systems providing an alternate mode based USB-C interface.

Order Code: S26391-F6058-L130

USB Type-C to DisplayPort Adapter



The FUJITSU USB Type-C to DP Adapter offers a fast and easy way to connect a DisplayPort-display to your mobile system, or desktop PC, using S26391-F6058-L201 the USB Type-C port via plug-and-play functionality

Order Code:

USB Type-C to VGA Adapter



The FUJITSU USB Type-C to VGA Adapter offers a fast and easy way to connect an analog VGA-display or projector to your mobile system, or desktop PC, using the USB Type-C port via plug-and-play functionality

Order Code: S26391-F6058-L203

USB Type-C to Gb-LAN Adapter



The FUJITSU USB Type-C to Gb-LAN Adapter offers a fast and easy way to connect a Gbit-LAN to your mobile system, or desktop PC, using the USB Type-C port via plug-and-play functionality

Order Code: S26391-F6058-L301

Wireless Keyboard Set LX410



The Wireless Keyboard Set LX410 is an excellent desktop solution for users with ambition. This durable keyboard set is equipped with 2.4 GHz technology and plug and play technology. The elegant mouse with new silent keys works on many surfaces due to its precise 1600 dpi sensor. It offers fabulous features and an ultra slim, portable design.

S26381-K410-L4** (**: country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO G5010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO G5010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use. html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-03-10 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH