



LED floor lamp MAULjura, dimmable



- **Continuously adjustable dimmer depending on the task and individual needs**
- **Powerful direct light (50%) on the work surface & indirect light (50%), room lighting**
- **Dual purpose: Direct light for the work surface and indirect light for room lighting**
- **Column and head made of high-quality aluminum**
- **Designed by MAUL: Developed and engineered in Germany**
- **GS mark, technical safety concept "Made by MAUL"**
- Convenient: Diffuser for minimal shadow casting
- Glare reduction to UGR <16 for fatigue-free viewing
- Zero power consumption when turned off thanks to the on/off switch
- Convenient: Removable power cord simplifies setup
- Switzerland: Also available with power cord (Swiss plug/IEC socket). Please add the abbreviation .CH to the item number
- IP20 protection rating
- Light source and ballast can be replaced by a qualified electrician
- Packaging made of cardboard, without plastic components

Illuminance of the : 1.960 lux illuminance at 85 cm distance, 1.220 lux illuminance at 110 cm distance
 Colour temperature per light source: 4.000 Kelvin (neutral white)
 Number of light sources: 7
 Energy efficiency class per light source: D (spectrum A to G)
 Weighted energy consumption per light source: 62 kWh/1000 h (2 x 16 kWh/1000 h & 5 x 6 kWh/1000 h)
 Service life L70B50 per light source: 50.000 h
 Useful luminous flux per light source: 9200 lm (2 x 2500 lm & 5 x 840 lm)
 Material: Head: Aluminium - Column: Aluminium
 Dimensions: Head: 60 x 26 x 3.5 cm - Column: 5 x 3.6 x 192 cm
 Movement: Head: fixed
 Position of the switch: Column

- Stable, solid steel base, 27 x 41 cm. Doesn't get in the way: The cut-out base plate can be positioned around a table leg. Height: 196.5 cm

Art. No.	Colour	EAN-Code	Tariff-No.	Base	Cable length (approx.)	Protection class	Pack size / PU	Weight (incl. packaging)	PU
8257102	white	4002390091435	94052190	base	2,50 m	I shock-proof plug	110,5 x 47,5 x 14,5 cm	13,286 kg	1 pc(s).
8257195	silver	4002390091428	94052190	base	2,50 m	I shock-proof plug	110,5 x 47,5 x 14,5 cm	13,286 kg	1 pc(s).