

USB C Multiport Adapter for MacBook Pro/Air - USB Type-C to 4K HDMI, 100W Power Delivery Pass-through, SD/MicroSD Slot, 2-Port USB 3.0 Hub - Portable USB-C Mini Dock

Product ID: DKT30CMHSDPD



This USB-C multiport adapter with HDMI turns your Macbook Pro, Macbook Air (including M1s), Google Pixelbook and other USB-C tablets and laptops into a workstation, anywhere you go. The USB Type-C multiport adapter provides 4K 30Hz HDMI video output, a USB Type-C port (data/power), one USB 3.2 Gen 1 Type-A (5Gbps) ports, an SD and MicroSD (uSD) Card Reader, all through a single connection to your laptop's USB-C or Thunderbolt 3 port.

It offers advanced charging through USB 100W Power Delivery 3.0 and eliminates the need for an attached cable with a retractable USB-C connection that connects directly to your USB-C host without the need for an attached cable.

The portable docking station supports a single HDMI monitor up to 4K 30Hz (3840 x 2160p) to create a powerful workstation. It can also connect to an ultrawide monitor.

The USB-C to USB 3.2 Gen 1 hub gives you one USB-C port and one USB-A port (BC 1.2 charging port) to connect your latest and legacy USB devices.

Access your multimedia content with ease. The multiport adapter provides direct access to your SD, SDHC and SDXC memory cards or microSD cards.

With support for USB Power Delivery 3.0 (up to 100W), the USB Type-C multiport adapter lets you power and charge your laptop, and power your peripherals when connected to a USB-C power adapter. The multiport adapter itself reserves 8W leaving up to 92W of power for charging.

The DKT30CMHSDPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery.

Certifications, Reports and Compatibility

Applications

Features

- **5-IN-1 FUNCTIONALITY:** USB-C multiport adapter with HDMI 4K 30Hz video output, USB 3.1/3.2 Gen 1 Hub 5Gbps with 1x USB-A (BC 1.2 fast charge) and 1x USB-C (Power + Data), SD and MicroSD (SD) card reader slots, and 100W Power Delivery
- **CABLE-FREE USB-C HOST CONNECTION:** Built-in retractable USB-C connector w/ a sliding switch for a tighter cableless connection on MacBook Pro 2018/2019, MacBook Air 2020 (Intel processor/M1 chip); designed to use 1 port, leaving a TB3 port for accessories
- **RELIABLE PERFORMANCE:** USB bus powered or via external USB-C power adapter; 100W Power Delivery 3.0 pass through with 8W reserved for adapter to avoid video flickering, device dropouts or overdrawing power common in other hubs; up to 92W for laptop charging
- **PORTABLE & COMPACT:** Docking station with slim design for easy transport in laptop bag with USB-C port conveniently recessed away, or optionally left connected to laptop for convenient on-the-go use, business travel or work from home
- **WIDE COMPATIBILITY:** Automatic driver installation for easy setup, this universal USB Type-C multiport adapter supports all major operating systems like Windows, macOS, iPadOS, Chrome OS; works w/ Thunderbolt 3 and USB-C tablets, Chromebooks, and laptops

Hardware

Warranty	3 Years
Fast-Charge Port(s)	Yes
Displays Supported	1
4K Support	Yes
Ports	4
Interface	USB 3.2 Gen 1
Bus Type	USB-C
USB Pass-Through	Yes
Chipset ID	VIA Labs - VL102 VIA Labs - VL817 Parade - PS176 NOREL Systems - NS1081C

Performance

Maximum Data Transfer Rate	5Gbps
Maximum Digital Resolutions	4K 30Hz
Type and Rate	USB 3.1 Gen 1 - 5 Gbit/s
Memory Media Type	SD/MMC (Secure Digital/Multimedia Card) microSD (Micro Secure Digital)

Connector(s)

External Ports	HDMI 1.4 USB 3.0 A (Fast-Charge, 9 pin) SD / MMC Slot MicroSD USB Type-C (Fast-Charge, 24 pin) USB 3.0
Host Connectors	USB Type-C (24 pin) USB 3.0 (5Gbps)

Software

OS Compatibility	macOS High Sierra (10.13), macOS Mojave (10.14), macOS Catalina (10.15), macOS Big Sur (11.0) macOS Monterey (12.0) Windows 8, Windows 10, Windows 11, Chrome OS, iPadOS, Android,
------------------	--

Power

Power Source	Bus Powered and Host USB-C Power Adapter
Power Delivery	100W
Power Consumption (In Watts)	8W

Environmental

Operating Temperature	0 to +70
Storage Temperature	-10 to +55



Humidity	5% to 90 % RH (no condensation)
----------	---------------------------------

Physical Characteristics

Product Length	1.4 in [35.0 mm]
Product Width	4.5 in [11.3 cm]
Product Height	0.4 in [10.5 mm]
Weight of Product	2.8 oz [78.0 g]

Packaging Information

Package Length	6.7 in [17.0 cm]
Package Width	5.6 in [14.2 cm]
Package Height	1.2 in [30.0 mm]
Shipping (Package) Weight	5.1 oz [145.0 g]

What's in the Box

Included in Package	USB Type-C Multiport Adapter
	Quick-Start Guide

**Product appearance and specifications are subject to change without notice.*

