## 90W external power adapter

**Shuttle**®

The Shuttle Accessory PE90 is an external AC to DC power adapter meant as a replacement device for certain Shuttle products. It provides a maximum output wattage of 90W.

## **Feature Highlight** AC power adapter (90W) with cable and DC Package output plug contents AC power cord with Europlug Quick guide Input Voltage: 100~240 VAC, 50~60 Hz Input Input Current: max. 1.5 A Output Voltage: 19 V DC Output Current: max. 4.74A Output Output Wattage: max. 90W Cooling Passive, fanless cooling DC connector: 5.5/2.5mm (outer/inner diameter) **Connectors** AC connenctor: angled Schuko safety plug (with earthing contact) Operation temperature range: 5~35 °C (41~95 °F) **Environ**mental Relative humidity range: 10~90% (non-condensing) Compliance and Logos: Safety/EMI CE, WEEE and others Dimensions: 127 x 51 x 30.5 mm (LWH) **Dimensions** Weight: 310 g (max.) Compatible to the 90W power adapter of the following Shuttle products: - Slim PCs: DS61, DS81, DS87, DH110(SE), DH170, DQ170, DH270, DH310(V2), DH310S, DH370, XH61(V), XH81(V), XH97V, XH110(V), XH170, XH310(R)(V) Backward compatible to the 65W power adapter of the following Shuttle products: - Slim-PC: DS47, DS407T, DS437(T), DS57U(x), DS67U(x), DS68U(x), DS77U(x), DS10U(x), XC60J Compatibility - Nano-PC: NC01U(x), NC02U(x), NC03U(x), NC10U(x) - All-in-One PC: X50, X50V4, X50V5(U3), X50V6(U3), X50V7(U3), P20U, P51U, P90U(3) - OMNINAS KD20, KD21, KD22 Backward compatible to the 40W power adapter of the following Shuttle products: - Slim-PC: XS35/XS36 series, DX30, DL10J - All-in-One PC: X50V2 (Plus), X50V3(L) - OMNINAS: KS10

## XPC Accessory PF9N





Images for illustration purposes only.



DH110 / DH170



**XH170V** 



**DS437** 

