Specifications

	Model		○ WM55R	○ WM65R	
	Diagonal Size		55"	65"	
	Type		60Hz New Edge	60Hz New Edge	
	Resolution		3,840 x 2,160 (Landscape)	3,840 x 2,160 (Landscape)	
	Brightness(Typ.)		350 (without glass), 220 (with glass)	350 (without glass), 220 (with glass)	
Panel	Contrast Ratio(Typ.)		4000:1 (Typ.)(without glass)	4000:1 (Typ.)(without glass)	
			4000-т (тур., (with four glass) 178:178	4000-1 (19)5/(Without glass)	
	Viewing Angle(H/V)				
	Operation Hour		16/7	16/7	
	Response Time(G-to-G)		8ms(Typ.)	8ms(Typ.)	
Sound	Speaker Type		Built in Speaker (10W x 2)	Built in Speaker (10W x 2)	
	INPUT	VIDEO	(Basic) HDMI 2, (With Tray) HDMI 3	(Basic) HDMI 2, (With Tray) HDMI 3	
		USB	(Basic) USB1, (With Tray) USB 2, USB External (In/Out)1	(Basic) USB1, (With Tray) USB 2, USB External (In/Out) 1	
Connectivity	OUTPUT	Touch Out	(Basic) Touch Out1 (USB Upstream Type), Audio Out1 (With Tray) Touch Out 2, Audio Out1, Screen Share(HDMI-Out)1	(Basic) Touch Out1 (USB Upstream Type), Audio Out1 (With Tray) Touch Out2, Audio Out1, Screen Share(HDMI-Out)1	
	INTERNAL	SENSOR	(Basic) Acceleration sensor (With Tray) Acceleration sensor, NFC	(Basic) Acceleration sensor (With Tray) Acceleration sensor, NFC	
	EXTERNAL	CONTROL	RS232C, LAN, WiFi/BT	RS232C, LAN, WiFi/BT	
	Туре		InGlass™	InGlass™	
	# of Drawing		Multi writing up to 4	Multi writing up to 4	
Touch	Touch Pen Type		Passive Pen with magnet	Passive Pen with magnet	
	Object Recognition Range	2	2mm/4mm/8mm/50mm, 1024 Level on Brush Mode	2mm/4mm/8mm/50mm, 1024 Level on Brush Mode	
	Touch Response Time		6.7ms	6.7ms	
	Туре		Internal	Internal	
	PowerSupply		AC100~240V50/60Hz	AC100~240V50/60Hz	
		Max[W/h]	154	181.5	
Power		Typical[W/h]	80	100	
Tower	PowerConsumption	Rating[W/h]	140	165	
	r ower consumption	Stand-by[W/h]	0.5	0.5	
		BTU[W/h]	525.14	618.915	
		Set	1297.4(W) x 768.2(H) x 59.9(D)	1522.4(W) x 897.6(H) x 62.9(D)	
	Dimension (mm)	Package	1464(W) x 915(H) x 190(D)	1691(W) x1055(H) x198(D)	
			1404(W) X 9 15(H) X 19U(D) 28.2	1691(W) X 1055(H) X 198(D) 40.0	
	Weight (kg)	Set	35.2	50.6	
		Package			
	Color		Light Gray	Light Gray	
Mechanical Spec	VESA Mount		400 x 400	400 x 400	
Spec	Protection Glass		Yes	Yes	
	Stand Type		Moving Stand, Wallmount	No-Gap Wall Mount	
	Rotation		Available with Flip moving stand (STN-WM55R) (Available with rotation support 3rd party accessory)	N/A with Flip No-Gap Wallmount (WMN-WM65R) (Available with rotation support 3rd party accessory)	
	Power Cable Length		3m	3m	
	Accessory		Cover-Jack	Cover-Jack	
	Operating Temperature		0°C~40°C	0°C~40°C	
Operation	Humidity		10~80%	10~80%	
	· · · · · · · · · · · · · · · · · · ·		Flip App		
	Key		1 11	Flip App	
	Special	H/W	Super Clear Coating, Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W x 2), WiFi Module Embedded	Super Clear Coating, Temperature Sensor, Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W x 2), WiFi Module Embedded	
	Special	S/W	Flip S/W	Flip S/W	
		Platform	Muse-M (Tizen 5.0)	Muse-M (Tizen 5.0)	
	Internal Player (Embedded H/W)	Processor	CA72 Quad(1.7GHz)	CA72 Quad(1.7GHz)	
Feature		On-Chip Cache Memory	L1 (I/D): 32KB / 32KB, L2 (Unified): 1MB	L1 (I/D): 32KB / 32KB, L2 (Unified): 1MB	
		Clock Speed	1.7GHz CPU Quad	1.7GHz CPU Quad	
		Main Memory Interface	LPDDR41.6GHz 64bit 2.5GB	LPDDR41.6GHz 64bit 2.5GB	
		Graphics	2D & 3D Graphics Engine - Up to 1920x1080. 32bpp - Supports OpenGLES"	2D & 3D Graphics Engine - Up to 1920x1080. 32bpp - Supports OpenGL ES	
		Storage	8GB(2.65GB Occupied by O/S, 5.35GB Available)	8GB(2.65GB Occupied by O/S, 5.35GB Available)	
		IO Ports	USB 2.0	USB 2.0	
		Operating System	Samsung Proprietary OS(VDLinux)	Samsung Proprietary OS(VDLinux)	
	Included		Passive Pen(2), Power Cable, Touch Out Cable (USB upstream)	Passive Pen(2), Power Cable, Touch Out Cable (USB upstream)	
		Stand	STN-WM55R	N/A	
Accessories		Stand Wallmount	STN-WM55R WMN4277SE	N/A WMN-WM65R	
Accessories	Optional				

•	Wallmount for WM55R			- WMN4277SE
	Dimension (mm)	Set	465(W) x 442(H) x 24.5(D) mm	1
Mechanical Spec	Dimension (mm)	Package	510(W) x 280(H) x 90(D) mm	
	Weight (kg)	Set	5.5	
		Package	6.8	
	Color		Black	
	VESA Mount		400 X 400	
	Rotation		N/A	
Accessories	Included		Installation Guide, Screws	

0		Wallm	ount for WM65R - WMN-WM65R
Mechanical Spec	Dimension (mm)	Set	520(W) x 280.3(H) x 15.9(D)
	Dimension (mm)	Package	594(W) x 337(H) x 75(D)
	\M/=:=b+/(!-=\	Set	1.75
	Weight (kg)	Package	3.2
	Color		Light Gray
	VESA Mount		400 X 400
	Rotation		N/A
Accessories	Included		Installation Guide, Screws
Feature	Special	H/W	No-Gap Spacing, Extra Bracket for strong fixation

•		Star	nd for WM55R - STN-WM55R
	Dimension (mm)	Set	835(W) x 1631.1(H) x 850.6(D)
		Package	1650(W) x 860(H) x 208(D)
	Weight (kg)	Set	34.5
Mechanical Spec		Package	41.5
	Color		Light Gray
	VESA Mount		400 X 400
	Rotation		Pivot Supports (90°)
Accessories	Included		Installation Guide, Screws
Feature	Special	H/W	Slim Design, No Assembly Required Installation

00		Tr	ay for Flip 2 - CY-TF65BRC	
	Dimension (mm)	Set	269.8(W) x 111.3(H) x 56.9(D)	
		Package	294(W) x 136(H) x 69(D)	
Mechanical Spec	Weight (kg)	Set	0.5	
-,		Package	0.7	
	Color		Light Gray	
			USB1	
			USB External (In/Out)1	
Connectivity	F 1 . C		Touch Out1	
Connectivity	Extra Connectivity Ports		HDMI-In1	
			HDMI-Out(Screen Share)1	
			NFC1	
Accessories	Included		Installation Guide, Screws	
Feature	Special	H/W	Easy install with dock connector Front facing connector for BYOD usage	

 $^{{\}rm ** Specifications \, on \, the \, table \, are \, flexible \, and \, subject \, to \, change \, under \, certain \, circumstances.}$