THINKVISION T24i

POWERFULLY VERSATILE FOR TODAY'S WORKFORCE



MODERN BUSINESS DISPLAY CRAFTED FOR PRODUCTIVITY

Power through your day with the Thinkvision T24i-2L. Its FHD In-Plane Switching panel and NearEdgeless bezels make it well suited for multi-monitor setups, helping you enhance efficiency. This TÜV Rheinland Eye Comfort and Eyesafe-certified monitor with **Natural Low Blue Light technology** is ideal for professionals as it reduces harmful blue light and minimizes eye fatigue and strain. Transfer or receive data with ease using varied options to connect other peripherals. This monitor is thoughtfully designed to keep your desk space organized and provide ergonomic benefits to users who spend long hours at work.

FEATURES OF THINKVISION T24i-2L



Impressive Display From Any Angle

The FHD In-Plane Switching panel does not distort content when viewed from any angle, up to 178° on either side, allowing everyone to work more accurately with greater details. The ThinkVision T24i-2L's ultra-thin NearEdgeless bezels maximize screen real estate and enable a seamless multi-monitor setup for easy multitasking and navigation of large documents.



Flexible Connectivity Options

Connect your accessories directly to the monitor through its four USB 3.2 Gen1 downstream ports. Power, video, and data peripherals, along with multiple options for display like VGA, DP1.2, and HDMI 1.4 ensure you experience seamless collaboration. Plug external speakers in through the Audio port for enhanced sound during meetings.



Comfortable Work Environment

The ThinkVision T24i-2L's minimized square base, phone holder, and flexible cable management system help you stay organized. Pivot, tilt, swivel, and lift your monitor for a comfortable setup all day long. Installing the monitor on a wall or separate mounting arms is easy with VESA mount compatibility. TÜV Rheinland Eye Comfort and Eyesafe certification, awarded by **Natural Low Blue Light technology**, signify that you can stay focused all day with reduced eye strain, while ensuring color accuracy and eliminating yellow distortion.

Think Vision T24i-2L

DISPLAY

Panel Size

23.8-inch

Screen Dimensions

535.0 mm x 313.0 mm

Panel Type

3-side NearEdgeless In-Plane Switching

Active Area

527.04 mm x 296.46 mm

Backlight

WLED

Aspect Ratio

16.9

Resolution

1920 x 1080

Pixel Pitch

 $0.2745 \times 0.2745 \text{ mm}$

Dot/Pixel Per Inch (DPI/PPI)

Viewing Angle (H x V @ CR 10:1)

178° / 178°

Response Time

4ms (Extreme Mode) 6ms (Normal Mode)

Refresh Rate

60 Hz

Brightness (typical)

250 cd/m²

Contrast Ratio (typical)

1000:1

Dynamic Contrast Ratio (typical)

3M:1

Color Gamut

72% NTSC (CIE 1931)

Color Support (typical)

16.7 Million

Anti-glare

Yes

CONNECTIVITY

Video Signal

1 x HDMI 1.4 1 x DP 1.2

1 x VGA

Audio Signal

1x Audio Out (3.5 mm)

USB Hub

Yes

USB Upstream

1 x USB 3.2 Gen1

USB Downstream

4 x USB 3.2 Gen1 (1 x BC 1.2)

MUITI-MEDIA

Optional Soundbar Support

Yes (PN: 0A36190)

POWFR

Power Consumption (typ./max.)

16W / 55W

Cable Management

Yes

Power Consumption

Power Consumption

ENERGY STAR Power

Consumption (P_{op}/E_{TEC})

AC 100 to 240 V (50-60 Hz)

Sleep/Off Mode

Switch-off Mode

13W / 46kWh

Power Supply

Voltage Required

MECHANICAL

Tilt Angle (front/back)

Swivel Angle (left/right)

VESA Mount Capability

Yes (100 x 100 mm)

Kensington Lock Slot

ThinkCentre M Series Tiny

Yes, by Tiny/Nano monitor

clamp II (PN: 4XH0Z42451)

and Tiny VESA mount II

(PN: 4XF0N03161)

< 0.5W

< 0.3W

Internal

-5° / 35°

150 mm

-90° / 90°

Support

Pivot

+45° / -45°

Lift (max. range)

Bezel Color

Raven Black

Bezel Width (side)

2.0 mm

Bezel Width (top/bottom)

2.0 mm / 22.2 mm

DIMENSION

Size Packed (D x H x W, mm/inch)

422.0 x 160.0 x 618.0mm 16.61 x 6.30 x 24.33 inches

Size Unpacked w/ Stand (D x H x W. mm/inch)

(lowest position) 205.0 x 409.3 x 539.8mm

8.07 x 16.11 x 21.25 inches

Size Unpacked w/ Stand (D x H x W, mm/inch) (highest position)

205.0 x 559.3 x539.8mm 8.07 x 22.02 x 21.25 inches

Size Unpacked w/o Stand (head only) (D x H x W, mm/inch)

44.1 x 326.5 x 539.8mm 1.74 x 12.85 x 21.25 inches

Weight Packed (kg/lbs.) 8.40kg / 18.52 lbs.

Weight Unpacked (kg/lbs.) 5.90 kg / 13.01 lbs.

Weight (monitor head only) (kg/lbs.)

3.65kg / 8.05 lbs.

WHAT'S IN THE BOX

Monitor with stand 1 x Power cable (1.8 m)

1 x DP cable (1.8 m) 1 x USB Type-A to B cable (1.8 m) Quick setup guide

CERTIFICATION

ENERGY STAR Rating

8.0

CCC Yes

TCO 8.0

TCO Edge 2.0

EPEAT Gold

RoHS (EU 2002/95/EC) Yes

Windows Certification Windows 7, Windows 10

China Energy Efficiency Standard

TÜV Rheinland Eye Comfort

Eyesafe Display Certification Yes











Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen1; 10 Gbit/s for USB 3.1 Gen2 & 20 Gbit/s for USB 3.2.

© 2021 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, and ThinkVision are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.