APC Dry Contact I/O SmartSlot Card

AP9613

O				

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and
	initiate actions on external devices.

Lead time

Main

Number of rack unit	ou
Provided equipment	User manual USB cable

Physical

Colour	Black
Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net weight	0.21 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Conformance

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6 ECC part 15 class A
	FCC part 15 class A

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1565 °C
Storage Relative Humidity	095 %

Storage altitude	0.0015240.00 m
Packing Units	
Package 1 Height	5.1 cm
Package 1 Width	23.5 cm
Package 1 Length	15.9 cm
Package 1 Weight	0.4 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.181 kg
Offer Sustainability	
Occadadora de la cassa de la c	Crear Paratism and dust

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Lead free	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

Contractual warranty

Warranty 2 years repair or replace