

## 5m Coax High Resolution Monitor VGA Video Cable with Audio HD15 M/M

Product ID: MXTHQMM5MA



The MXTHQMM5MA 5-meter High Resolution VGA Cable with Audio is a high quality SVGA cable designed to provide the highest video quality possible through VGA - a single cable solution for connecting both video between a VGA video card and monitor, and audio connections between a sound card and external audio device.

StarTech.com's high resolution VGA cable with audio features high quality male-to-male coaxial VGA cable, and is designed to eliminate picture "ghosting" and fuzzy images that are inherent to non-coaxial cables, while providing superior EMI interference protection by using ferrite cores near the connector ends.

The 5-meter SVGA cable (VGA Cable with Audio) is backed by StarTech.com's Lifetime Warranty.

### Certifications, Reports and Compatibility



### Applications

- Make video and audio connections using a single cable
- Ideal for high resolution VGA monitors (1920x1200 and above)

### Features

- Triple-coaxial + twisted-pair wire for crystal clear display
- Impedance matched at 75 Ohms for full brightness and vibrant picture color
- Molded connector ends with strain relief
- Ferrite core eliminates EMI interference

|                                 |                           |  |
|---------------------------------|---------------------------|--|
| <b>Hardware</b>                 | Warranty                  | Lifetime   |
|                                 | Cable Jacket Type         | PVC - Polyvinyl Chloride   |
|                                 | Cable Shield Type         | Aluminum-Mylar Foil with Braid                                     |
|                                 | Connector Plating         | Nickel   |
|                                 | Fire Rating               | CMG Rated (General Purpose)  |
|                                 | Number of Conductors      | 14   |
|                                 | Number of Ferrites        | 2  |
|                                 | Regulatory Approvals      | UL2919   |
| <b>Performance</b>              | Impedance                 | 75 Ohm   |
| <b>Connector(s)</b>             | Connector A               | 1 - 3.5 mm Mini-Jack (3 Position) Male                             |
|                                 |                           | 1 - VGA (15 pin, High Density D-Sub) Male                          |
|                                 | Connector B               | 1 - 3.5 mm Mini-Jack (3 Position) Male                             |
|                                 |                           | 1 - VGA (15 pin, High Density D-Sub) Male                          |
| <b>Environmental</b>            | Humidity                  | 0 - 80 %RH   |
|                                 | Operating Temperature     | 0 to 60 °C   |
|                                 | Storage Temperature       | -20 to 80 °C   |
| <b>Physical Characteristics</b> | Cable Length              | 5 m [16.4 ft]  |
|                                 | Color                     | Black  |
|                                 | Connector Style           | Straight   |
|                                 | Product Length            | 5 m [16.4 ft]  |
|                                 | Weight of Product         | 592 g [20.9 oz]  |
|                                 | Wire Gauge                | 28 AWG   |
| <b>Packaging Information</b>    | Package Height            | 62.5 cm [24.6 in]  |
|                                 | Package Length            | 25.5 cm [10 in]  |
|                                 | Package Quantity          | 1  |
|                                 | Package Width             | 56 mm [2.2 in]   |
|                                 | Shipping (Package) Weight | 0.6 kg [1.3 lb]  |
| <b>What's in the Box</b>        | Included in Package       | 1 - 5 m Coax High Resolution Monitor VGA Cable with Audio HD15 M/M |

Product appearance and specifications are subject to change without notice.