

15m DVI-D SLD Dual Link Cable, Gold Line

Part No.: 36207



Description

- Advanced, high performance DVI-D Dual Link cable with gold design connector
- Supports DVI resolutions up to 2560x1600@60Hz and HD resolutions up to 1080p
- Low attenuation design with 24K gold plated contacts for signal integrity and long distance transmission
- Metal connector greatly reduces interference and provides increased EMC shielding without the need for a ferrite core
- 25 year warranty

From the Lines cable connectivity concept developed by Lindy, Gold Line DVI-D Dual Link cables are the no compromise, high performance connection solution for use in the most demanding professional environments.

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long distances.

For complete signal integrity, Gold Line DVI-D Dual Link cables feature 24K gold plated contacts, triple shielding with 100% aluminium mylar wrap and an 85% tinned copper braid.

Gold Line DVI-D Dual Link cables support DVI resolutions up to 2560x1600@60Hz including HD resolutions up to 1080p.

Gold Line DVI-D Dual Link cables are available in 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m and 25m lengths.

Technical details

Connectors:

- Connector A: DVI-D Male (Dual Link)
- Connector B: DVI-D Male (Dual Link)
- Housing Material: 24K Gold Plated Metal
- Connector Plating: 24K Gold 3µm
- Pin Construction: Phosphor Bronze

- Pin Plating: 24K Gold 15µm
- Dimensions (approx.) WxDxH: 39.5x16.5x44.5mm (1.55x0.65x1.73in)

Cable Construction:

- Length: 15m (49.21ft)
- Standard: DVI-D Dual Link
- Colour: Grey
- Type: Round
- Jack Diameter: 11.5mm (0.45in)
- Jacket Material: PVC
- Conductor Material: OFC Copper
- Conductor Gauge: 24AWG
- Shielding: Copper Braid 85%

Specifications:

- Supported Bandwidth: 9.9 Gbps
- Maximum Resolution: 2560x1600@60Hz
- Nominal Attenuation: 1 - 825Mhz < 8db
- Minimum Bend Radius: 126mm (4.96in)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)

Miscellaneous:

- Packaging Type: Polybag
- Warranty (Years): 25
- Certificated: RoHS, REACH, UL

Purchasing Information:

- No. 36207
- EAN: 4002888362078
- This product is also available in other lengths: 36208 - 20m (65.62ft), 36209 - 25m (82.02ft)