

RACK PDU, BASIC, 0U/1U, 120-240V/15A, 220-240V/10A, (8) C13

AP6015A

Overview	
Lead time	
Main	
Main Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Main Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Provided equipment	Installation guide Safety guide
Physical	
Colour	Black
Height	24 cm
Height Width	24 cm 4.4 cm
Width	4.4 cm
Width	4.4 cm 9.3 cm
Width Depth Net weight	4.4 cm 9.3 cm 0.91 kg Front
Width Depth Net weight Mounting location	4.4 cm 9.3 cm 0.91 kg Front Rear
Width Depth Net weight Mounting location Mounting preference	4.4 cm 9.3 cm 0.91 kg Front Rear No preference
Width Depth Net weight Mounting location Mounting preference Mounting mode	4.4 cm 9.3 cm 0.91 kg Front Rear No preference
Width Depth Net weight Mounting location Mounting preference Mounting mode	4.4 cm 9.3 cm 0.91 kg Front Rear No preference Not rack-mountable
Width Depth Net weight Mounting location Mounting preference Mounting mode Input [In] rated current	4.4 cm 9.3 cm 0.91 kg Front Rear No preference Not rack-mountable

Load capacity	2300 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets 8 IEC 60320 C13

Conformance

cUL listed CE EAC IRAM UL listed VDE Product certifications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	13 cm
Package 1 Length	21 cm
Package 1 Weight	1.37 kg
Number of Units in Package 3	192
SCC14	10731304327797

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace