

482.6 mm (19") installation system

Imperial installation

Adaptor, metric to 21"/19"

With this adaptor, 482.6 mm (19") assemblies may be fastened to metric (535 mm) mounting angles, or combined systems may be configured.

Material:

- Extruded aluminium section

Units U	Height SU	Packs of	Model No.
1	2	2 pc(s).	7246.010
3	6	2 pc(s).	7246.030
6	11	2 pc(s).	7246.060



Drawer

for one 482.6 mm (19") mounting level


For front attachment to mounting angles, 482.6 mm (19"). With cover and telescopic slides to accommodate assignment lists, operating manuals and small parts. The small version of the 2 U variant is also suitable for mounting inside a swing frame.

Material:

- Sheet steel

Supply includes:

- Fully assembled
- Security lock 12321
- Assembly parts



Units U	Width	Clearance openings, width mm	Clearance openings, depth mm	Installation depth mm	Colour	Packs of	Model No.
2	19"	411	419	427	RAL 7035	1 pc(s).	7282.035
2	19"	411	244	250	RAL 7035	1 pc(s).	7282.135
3	19"	411	419	427	RAL 7035	1 pc(s).	7283.035
2	19"	411	419	427	RAL 9005	1 pc(s).	5502.305
3	19"	411	419	427	RAL 9005	1 pc(s).	5502.325

Small equipment box, 4 U, shielded

for one 482.6 mm (19") mounting level

For accommodation of small equipment and other accessories within a partitioned 482.6 mm (19") installation level. The small equipment box contains an adjustable mounting base which can be used to further sub-divide the box.

Material:

- Sheet steel
- Brush strip: Plastic, UL 94-HB

Surface finish:

- Spray-finished

Colour:

- RAL 9005

Load capacity:

- 200 N surface load, static

Supply includes:

- Small equipment box with brush strip
- 1 shelf



Contact surface, width mm	Contact surface, depth mm	Height mm	Width mm	Depth mm	Packs of	Model No.
405	300	170	427	400	1 pc(s).	5501.900