



Delock Adapter USB Type-C™ > 1 x Serial DB9 RS-232

Description

This USB Type-C™ to serial adapter by Delock provides a compatible RS-232 DB9 interface for printers, measuring instruments, controllers, IoT devices etc.



ca. 1,8 m

Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x serial RS-232 DB9 male
- Chipset: Prolific PL2303 HXD
- Screw type: #4-40 UNC
- Compatible with USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 1 Mbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bit: 1, 1.5, 2
- Data bit: 5, 6, 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 512 Byte buffer bi-directional
- Cable length: ca. 1.8 m

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.31 / Kernel 4.x.x, Mac ex OS 10.12, Android ex 4.4
- PC or laptop with a free USB Type-C™ or Thunderbolt™ 3 port

Package content

- Adapter cable USB Type-C™ > 1 x Serial RS-232 DB9
- Driver CD
- User manual

Item no. 62964

EAN: 4043619629640

Country of origin: HONG KONG

Package: Retail Box



Images





General	
function:	standard Plug & Play
Specification:	standard RS-232 USB 1.1 USB 2.0
Supported operating system:	standard ex Android 4.4 Linux ex Kernel 3.3 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
Interface	
connector 1:	standard 1 x USB Type-C™ male
connector 2:	standard 1 x Serial RS-232 DB9 male
Technical characteristics	
Chipset:	standard Prolific PL2303HXD
Data transfer rate:	standard up to 921.6 Kbps
FIFO:	standard 512 byte
Signal transmission:	standard TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	standard asynchronous full duplex
Voltage:	standard USB Bus powered (no additional power supply required)
Physical characteristics	
Cable length incl. connector:	standard 1.8 m
Screw type:	standard #4-40 UNC
Colour:	standard black