

7-Port USB-C Hub - USB-C to 5x USB-A and 2x USB-C - USB 3.0

Product ID: HB30C5A2CSC



This USB-C™ hub turns your laptop or desktop USB Type-C™ or Thunderbolt™ 3 port into four standard USB-A ports, one USB-A fast-charge port, and two USB-C ports. You can also extend the range of your USB devices by using this hub as a mid-point repeater.

Connect more devices, quickly and easily

The 7-port USB hub provides convenient port access. The extended length of the supplied cable offers the flexibility to position your hub and USB devices as needed, in order to create a comfortable, space-efficient work area. The ports are sufficiently spaced to plug or unplug your USB devices without needing to disconnect other devices from neighboring ports.

With extra USB 3.0 ports, you can increase productivity and connect more devices to your computer, or avoid the hassle of swapping connected devices on your port-limited laptop.

The hub lets you extend the life of your current USB 3.0 devices while also taking advantage of newer USB-C devices.

Charge-and-sync your mobile devices

With the available fast-charge port, the hub helps to ensure that your tablet or smartphone are charged and ready to use when you need them. You can also sync and access your device while it's charging. The USB-A charge port supports USB Battery Charging Specification 1.2.

The HB30C5A2CSC is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Upgrade and expand the connection capabilities of your MacBook, Ultrabook™, laptop, or desktop
- Deploy in hot-desk environments to provide USB hub access for multiple devices
- Connect a wide variety of peripherals at home or in the office, all from a single USB 3.0 connection

Features

- 1-meter cable enables flexible positioning of the hub and USB devices on your desk
- Connect up to seven USB 3.0 devices to a single USB-C port on your computer: two USB-C devices and five USB-A devices
- USB 3.0 charge-and-sync port can charge your device with or without a host connection
- All ports are backward compatible with older USB 2.0 and 1.1 devices
- Supports easy plug-and-play installation, hot-swapping or hot-plugging
- All ports are compliant with USB 3.0 and data rates up to 5Gbps
- Integrated physical On/Off power button

| | | | |
|---------------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hardware | Warranty | 2 Years | |
| | Bus Type | USB 3.0 | |
| | Chipset ID | VIA/VLI - VL813 | |
| | Industry Standards | USB Battery Charging Specification Rev. 1.2 USB-A charging port delivers up to 1.5 amps of power USB 3.0 - Backward compatible with USB 2.0 and 1.1 | |
| | Interface | USB 3.0 | |
| | Ports | 7 | |
| | USB-C Device Port(s) | Yes | |
| | USB-C Host Connection | Yes | |
| Performance | Maximum Data Transfer Rate | 5 Gbps | |
| | Supported Charging Modes | Charging Downstream Port (CDP) Dedicated Charging Port (DCP) | |
| | Supported Charging Outputs | BC 1.2 (1.5A) | |
| | Type and Rate | USB 3.0 - 5 Gbit/s | |
| | UASP Support | Yes | |
| Connector(s) | Connector Type(s) | 4 - USB Type-A (9 pin) USB 3.0 Female 2 - USB Type-C (24 pin) USB 3.0 Female 1 - USB 3.0 A (Fast-Charge, 9 pin, SuperSpeed) Female 1 - USB Type-B (9 pin) USB 3.0 Male | |
| | Software | OS Compatibility | OS Independent; No additional drivers or software required |
| | Special Notes / Requirements | Note | The USB Type-C ports are data only. USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. The hub does not support DP Alt Mode or USB Power Delivery. |
| | | System and Cable Requirements | Available USB Type-C port - USB 3.0 (5Gbps) |
| Indicators | LED Indicators | 7 - Active | |
| Power | Center Tip Polarity | Positive | |
| | Input Current | 1 A | |
| | Input Voltage | 100 ~ 240 AC | |
| | Output Current | 4 A | |
| | Output Voltage | 12 DC | |
| | Plug Type | M | |

| | | |
|---------------------------------|------------------------------|--------------------------------------------------|
| | Power Consumption (In Watts) | 48 |
| | Power Source | AC Adapter Included |
| Environmental | Humidity | 0~95% RH (Non-condensing) at 25°C |
| | Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| | Storage Temperature | -20°C to 70°C (-4°F to 158°F) |
| Physical Characteristics | Cable Length | 3.3 ft [1 m] |
| | Color | Black & Silver |
| | Enclosure Type | Plastic |
| | Form Factor | Desktop |
| | Product Height | 0.9 in [24 mm] |
| | Product Length | 5.9 in [149 mm] |
| | Product Weight | 8.8 oz [250 g] |
| | Product Width | 2.6 in [65 mm] |
| Packaging Information | Shipping (Package) Weight | 21.2 oz [600 g] |
| What's in the Box | Included in Package | 1 - USB-C hub |
| | | 1 - 1m USB-C to USB-B cable |
| | | 1 - universal power adapter (NA/JP, UK, EU, ANZ) |
| | | 1 - quick-start guide |

Product appearance and specifications are subject to change without notice.