



0.8m USB 4 Type C Cable, 40Gbps, Anthra Line

No.: 36947

Type C Male to C Male

Description

- Professional choice USB 4 Gen 3x2 Type C to C cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 40Gbps (backwards compatible to USB 3.2 , USB 2.0 and Thunderbolt 3)
- Supports DisplayPort 2.0 Alternate Mode and USB Power Delivery 3.0 up to 100 Watt (20V 5A)
- Triple shielded coaxial cable, gold plated contacts and nickel plated connectors
- 2 year warranty

The Anthra Line USB 4 Type C to C cable from Lindy's Cable Lines concept is the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 4 cables are premium connections that feature triple shielded construction with silver plated copper conductors for performance and corrosion resistance. High quality gold plated contacts and nickel plated connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 40Gbps are supported for rapid transfer of large data volumes. These cables are E-marked to provide 100W [5A] of power to devices using the most efficient power delivery profiles.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Technical details

Connectors

- Connector A: USB 4 Type C Male
- Connector B: USB 4 Type C Male
- Chipset: EJ913D
- Housing Material: TPE
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions [approx.] WxDxH: 30x12.4x6.5mm [1.18x0.49x0.26in]

Cable Construction

- Length: 0.8m [2.62ft]
- Standard: USB 4 Gen 3x2
- Colour: Black

- Type: Round
- Jacket Diameter: 4.8mm [0.19in]
- Jacket Material: TPE
- Conductor Material: Silver plated copper
- Conductor Gauge Power: 23AWG
- Conductor Gauge Data: 30AWG/33AWG/34AWG
- Shielding: Tinned Copper Braid 85%

Specifications

- Supported Bandwidth: 40Gbps
- Maximum Resolution: 8K@60Hz
- Nominal Attenuation: 0.5Mhz-15Ghz \leq 11dB
- Minimum Band Radius: 28.8mm [1.13in]
- Operating Temperature: -20°C - 40°C [-4°F - 104°F]
- Storage Temperature: -40 °C - 80°C [-40°F - 176°F]

Miscellaneous

- Packaging Type: Polybag
- Warranty [Years]: 2
- Certificated: RoHS, REACH, California Proposition 65, UL

Purchasing Information

- No.: 36947
- EAN: 4002888369473