Rittal - The System.

Faster – better – everywhere.

CMC III CAN bus connection cable – DK 7030.480

Date: Jul 12, 2021



CMC III CAN bus connection cable - DK 7030.480

created: 12.07.2021 on www.rittal.com/com-en



D I	4		4.5
Prod	uct	descri	ntion
riou	uci	uescii	มแบเ

Description: For connecting the PU to the CAN bus sensors III, units III and control units III as a bus,

also for cabling together. Because it is available in different lengths, the CMC III system

can be adapted to various applications and built to a custom design.

Applications: For connecting the CAN bus units.

Information and power transfer of the individual CAN bus units.

Product description

Dimensions: Length: 3 m

Operating temperature:

Operation (environment): +0 °C...+55 °C

Ambient humidity (non-condensing):

Operation (environment): 5 % - 95 %

Interfaces/connections: Connector (type): RJ45

Connector (type): RJ45

Packs of: 1 pc(s).

Weight/pack: 0.13 kg

Copper weight (kg per

piece):

0

EAN: 4028177695924

Customs tariff number: 85444290

© Rittal 2021

ETIM 7.0:	EC000313	
ETIM 6.0:	EC000313	
e Cl@ss 8.0/8.1:	27189253	
e Cl@ss 6.0/6.1:	27189253	
Product description:	DK CMC III CAN bus connection cable, L: 3 m, type: RJ45	
Approvals		
Certificates:	NA	

© Rittal 2021