

# Product datasheet

Specifications

**APC**



## APC Service Bypass Panel 200/208/230/240V 125A HW Input/ Output

SBP20KP

### Overview

Lead time

### Main

<b>Main Input Voltage</b>	200 V
	208 V
	220 V
	230 V
	240 V
	380 V 3 phases
<b>Main Output Voltage</b>	400 V 3 phases
	415 V 3 phases
	200 V
	208 V
	220 V
<b>Output connector type</b>	230 V
	240 V
	Hard wire 3-wire (H N + E) 1 Hard wire 3-wire (2P + E) 1
<b>Number of rack unit</b>	4U
<b>Number of cables</b>	1
<b>Provided equipment</b>	Installation guide Rack mounting brackets User manual

### Physical

<b>Colour</b>	Black
<b>Height</b>	17.8 cm
<b>Width</b>	43.2 cm
<b>Depth</b>	55.4 cm
<b>Net weight</b>	19.32 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	Lower
<b>Mounting mode</b>	Rack-mounted

### Input

<b>Network frequency</b>	50/60 Hz
<b>Number of input connectors</b>	1 hard wire 3-wire (H N + E) 1 hard wire 3-wire (2P + E) 1 hard wire 5-wire (3P + N + E)

Permissible voltage	200...240 V
Max line current	125 A
Input current limits	125 A
Load capacity	20000 VA
Power factor	0...1

## Output

Max current draw	125 A
Protection type	Circuit breaker
Efficiency	99 %

## Conformance

Product certifications	CSA GOST
------------------------	-------------

## Environmental

Ambient air temperature for operation	-20...50 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-40...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	84.5 cm
Package 1 Length	61 cm
Package 1 Weight	31.36 kg

## Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

## Contractual warranty

Warranty	2 years (parts only)
----------	----------------------

## Recommended replacement(s)