



USB Type C, mDP & DisplayPort to HDMI 18G Converter Tether

No.: 38304

Connect a Type C, mDP or DP source device to a securely fitted HDMI cable

Description

- Connects a Type C, Mini-DP or DP source device to a securely fitted HDMI cable
- High-quality stainless-steel ring with all connectivity options
- Fitted with a cable clamp for securing the HDMI cable
- Supports resolutions up to 4K@60Hz 4:4:4 8bit
- 2-Year Warranty

Converter tethers are compact, secure solutions for equipping the correct converter to a secure display cable, providing simple connectivity for different users and source devices.

The Lindy USB Type C, mDP & DisplayPort to HDMI 18G Converter Tether is a superior, multi-av solution with separate USB Type C, Mini DP and DisplayPort to HDMI converters, all fitted securely to a 15cm diameter stainless-steel tether for easy access when required. With a built-in clamp which fits around the display's HDMI cable*, this tether is perfect for presentation or collaborative environments where different users will have a variety of source devices and connections. This ensures the adapters are also fixed in place ready for the next user.

With active chipset conversion each converter provides enhanced compatibility with many different source connections and graphics cards including PCs, notebooks and tablets. Supporting resolutions up to 3840x2160@60Hz 4:4:4 8bit, each converter ensures a premium viewing experience, perfect for immersive learning experiences in classrooms, engaging conference room displays or field-based demonstrations and training.

*The HDMI cable clamp will fit cables up to approx. 8mm [0.31in] diameter

Technical details

Specifications

- AV Interface: USB Type C, Mini DisplayPort, DisplayPort to HDMI
- Interface Standard: DisplayPort 1.2, HDMI 2.0
- Supported Bandwidth: 18Gbps
- Maximum Input Resolution: 3840x2160@60Hz 4:4:4 8Bit
- Maximum Output Resolution: 3840x2160@60Hz 4:4:4 8Bit
- Chipset: DisplayPort : PS176, mDP: PS176, USB Type C: VL100 + PS176
- HDCP Support: 2.2
- Supported Audio: Digital Audio Pass-through

- Separate Audio Ports: -
- Special Features: -

Connectors

- Input : USB Type C (Male), Mini DisplayPort (Male), DisplayPort (Male)
- Output : HDMI Type A (Female)

Physical Properties

- Dimensions (approx.) WxDxH: USB Type C Connector: 7.6x25x6.6mm [0.3x0.98x0.26in] to HDMI: 37x42x12mm [1.46x1.65x0.47in]
Mini DP Connector: 20x26x9.5mm [0.79x1.02x0.37in] to HDMI: 45x45x15mm [1.77x1.77x0.59in]
DisplayPort Connector: 31.5x20x9mm [1.24x0.79x0.35in] to HDMI:45x45x15mm [1.77x1.77x0.59in]
- Cable Length:
USB Type C to HDMI: 125mm [4.92in]
Mini DP to HDMI: 135mm [5.31in]
DP to HDMI: 120mm [4.72in]
- Housing Material: Plastic
- Jacket Material: PVC
- Jacket Diameter: DisplayPort & mDP: 5mm [0.2in], USB Type C: 4mm [0.16in]
- Minimum Bend Radius: DisplayPort & mDP: 55mm [2.17in], USB Type C: 40mm [1.57in]
- Net Weight: 0.08kg [0.18lb]
- Operating Temperature: 0°C - 45°C [32°F - 113°F]
- Storage Temperature: -10°C - 70°C [14°F - 158°F]
- Humidity: 10 - 90% RH [non-condensing]
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 236x255mm [9.29x10.04in]
- Gross Weight: 0.1kg [0.22lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

Package Contents

- USB Type C, mDP & DisplayPort to HDMI 18G Converter Tether
- PH0x75 Screwdriver

Purchasing Information

- No.: 38304
- EAN: 4002888383042