



**34" VA UWQHD curved monitor with a built-in Windows Hello camera and microphone, USB-C Dock, LAN, KVM-Switch and 15cm height adjustable stand**

Meet the XCB3497WQSNPH — a 34" curved all-in-one monitor designed for effortless efficiency. With a built-in KVM switch and USB-C dock, you can seamlessly control multiple devices and connect your laptop with a single cable. The vibrant VA panel delivers stunning colors, deep contrast, and wide viewing angles for an immersive experience. Plus, smart features like a 5MP autofocus webcam with Windows Hello, a height-adjustable ergonomic stand, and eye-care technologies keep you comfortable and productive all day.



**USB-C Dock**

The dock allows you to connect your laptop with a single cable to the monitor to both make sure it is charged and connected to a wired network and signal from the laptop is sent to the monitor. With additional USB-ports, your mouse, keyboard or webcam can also be connected to the monitor. All thanks to a single cable connecting your laptop\* to the USB C dock in the monitor.

\*Functions vary depending on your laptop USB-C support.



**KVM SWITCH**

Having a monitor with a KVM switch allows you to share the devices connected via USB to your monitor with two different PCs. Just change the signal input in the OSD menu of the monitor and your keyboard, mouse and webcam will switch from your work laptop to your gaming PC.

## 01 DISPLAY CHARACTERISTICS

<b>Design</b>	curved
<b>Diagonal</b>	34", 68.7cm
<b>Panel</b>	VA panel, matte finish
<b>Curved</b>	1500R
<b>Native resolution</b>	3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C)
<b>Aspect ratio</b>	21:9
<b>Panel brightness</b>	350 cd/m <sup>2</sup>
<b>Static contrast</b>	3000:1
<b>Advanced contrast</b>	80M:1
<b>Response time (MPRT)</b>	0.4ms
<b>Viewing zone</b>	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
<b>Colour support</b>	16.7mIn 8bit (sRGB: 99%; NTSC: 72%, DCI-P3 >90%)
<b>Horizontal Sync</b>	30 - 180kHz
<b>Viewable area W x H</b>	797.2 x 333.7mm, 31.3 x 13.1"
<b>Pixel pitch</b>	0.232mm
<b>Colour</b>	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

<b>Signal input</b>	HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x 1440@ 120Hz) USB-C x1 (3440 x 1440@ 120Hz, PD 95W)
<b>USB HUB</b>	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
<b>USB-C DOCK</b>	x1 (Power delivery 95W, LAN, USB v.3.2 (Gen 1, 5Gbit))
<b>HDCP</b>	yes
<b>Headphone connector</b>	yes
<b>RJ45 (LAN)</b>	x1

## 03 FEATURES

<b>KVM switch</b>	yes
<b>Blue light reducer</b>	yes
<b>Flicker free</b>	yes
<b>Adaptive Sync support</b>	FreeSync Premium HDMI: 2560 x 1440 @48-100Hz, DP / USB-C: 3440 x 1440 @48-120Hz
<b>Extra</b>	Built-in 5MP webcam with autofocus, microphone and privacy shutter compliant with Windows Hello
<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
<b>Control buttons</b>	Joystick: Power/ Menu (Centre), Forward/ Signal Select, Backward, Left/ i-Style colour/ ECO/ BlueLight Reducer, Right/ Volume
<b>User controls</b>	picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, Mac address, USB charge, USB C speed), KVM (HDMI1, HDMI2, DisplayPort, USB C), input select, audio settings (volume, mute audio), webcam, recall
<b>Speakers</b>	2 x 5W
<b>Convenience</b>	Kensington-lock™ prepared, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

## 05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI, DP, USB-C
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	55W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to <a href="http://www.epeat.net">www.epeat.net</a> for details
REACH SVHC	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	807 x 443 (592.5) x 239.5mm
Box dimensions W x H x D	940 x 500 x 198mm
Weight (without box)	9.7kg
Weight (with box)	14.2kg
EAN code	4948570125296

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED