ViewSonic

VG3419C

Key **Features**

- UWQHD 3440 x 1440 resolution on a 21:9 ultra-wide screen
- Integrated Docking Station with USB Type-C and Ethernet
- 1500R Curved Panel
- 120Hz AMD FreeSync™ Premium for smooth, continuous visuals
- Advanced ergonomics with height adjustment and a -3.5°~23° tilt angle

Product **Description**

With a 34" curved screen and stunning UWQHD resolution (3440 x 1440), the ViewSonic VG3419C monitor elevates your viewing experience to immersive excellence. Offering USB-C and Ethernet connectivity, this curved docking monitor dubs as a complete hub for charging, data, network, and peripherals, reducing clutter and simplifying cable management. With ergonomic flexibility, you can tilt and adjust the height of the VG3419C to have a smooth workflow as a professional multitasker. Thought for multi-tasking and productivity, the VG3419C comes with a built-in KVM switch function to connect and control multiple systems.

Visit Us   www.viewsonic.com

DISPLAY

Display Size (in.):	34
Viewable Area (in.):	34
Panel Type:	VA Technology
Resolution:	3440 x 1440
Resolution Type:	UWQHD (UltraWide QHD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	300 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	21:9
Response Time (Typical GTG):	3.5ms
Response Time (GTG w/OD):	3.5ms
Response Time (MPRT):	0.4ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	1500R
Refresh Rate (Hz):	120
Variable Refresh Rate Technology:	FreeSync Premium
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 86% size (Typ) sRGB: 121% size / 100% coverage (Typ)
Pixel Size:	0.232 mm (H) x 0.232 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3440x1440
Mac® Resolution (max):	3440x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3440x1440

CONNECTOR

USB 3.2 Type A Down Stream:	3
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (65W power charger)
3.5mm Audio Out:	1
HDMI 2.0:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
Ethernet LAN (RJ45):	1

AUDIO

Internal Speakers:	2Watts x2

POWER

Eco Mode (Conserve):	42W
Eco Mode (optimized):	49W
Consumption (typical):	56W
Consumption (max):	66W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Joystick key: Up, Right, Down, Left, Center; Shortcut: Input Selet, Volume Up, Volume Down, Power
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 30 ~ 160KHz, DisplayPort (v1.4): 30 ~ 185KHz, Type C: 30 ~ 185KHz
Frequency Vertical:	HDMI (v2.0): 24 ~ 120Hz, DisplayPort (v1.4): 24 ~ 120Hz, Type C: 24 ~ 120Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C

ERGONOMICS

Height Adjust (mm):	150
Tilt (Forward/Back):	-3.5º / 23º

WEIGHT (IMPERIAL)

Net (lbs):	23.4
Net Without Stand (lbs):	14.9
Gross (lbs):	29.8

WEIGHT (METRIC)

Net (kg):	10.6
Net Without Stand (kg):	6.8
Gross (kg):	13.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	38.6 x 20.7 x 8.8
Physical (in.):	31.9 x 17.47~23.38 x 10.6
Physical Without Stand (in.):	31.9 x 14.4 x 4.2

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	980 x 526 x 224
Physical (mm):	809 x 443.8~593.8 x 269
Physical Without Stand (mm):	809 x 366 x 107

GENERAL

Regulations:	Energy Star, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA
PACKAGE CONTENTS:	VG3419C x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards