

Overview

HP mt45 Mobile Thin Client



Left

- | | |
|------------------------------------|---|
| 1. HD and IR Camera (Optional) | 7. Clickpad |
| 2. Ambient Light Sensor (Optional) | 8. Smartcard Reader (Optional) |
| 3. IR Camera LEDs (Optional) | 9. USB 3.1 Gen 1 Charging Port |
| 4. Internal Microphones | 10. Vents |
| 5. HP Privacy Camera Shutter | 11. Security Lock Slot (Lock sold separately) |
| 6. HD Camera LED | 12. Power Button |

Overview



Right

- | | |
|-----------------------------------|---|
| 1. Power Connector | 6. USB 3.1 Gen 1 Port |
| 2. USB Type-C™ | 7. Audio Combo Jack |
| 3. Docking Connector | 8. SIM Card Slot¹ |
| 4. Ethernet Port | 9. Touch Fingerprint Sensor (Optional)² |
| 5. HDMI Port (Cable not included) | 10. Pointstick |

¹All units have a SIM card slot and icon but units that do not support WWAN are shipped with a non-removable SIM slot plug

²To verify you have a fingerprint reader and not a plug, press the Windows key on your keyboard, select Settings, select Accounts, and then select Sign-in options and follow the on-screen instructions.

Overview

AT A GLANCE

- Eye-catching Ultraslim design, premium precision-crafted machined aluminum (CNC), seamless formed aluminum chassis for clean, crisp, premium look and feel
- Preinstalled with Windows 10 IoT Enterprise 2019 or HP ThinPro/Smart Zero Core
- 2nd Generation AMD Ryzen™ 3 PRO 3300U Mobile processor with Radeon™ Vega Graphics
- 128 GB Flash storage and optional 4GB (HP ThinPro OS only) or 8 GB memory
- Choice of 35.6cm (14") diagonal FHD IPS anti-glare LED-backlit, slim narrow border or ultra-slim display:
 - (1920 x 1080) UWVA, 250-nit, 45% CG, eDP, narrow border, slim
 - (1920 x 1080) UWVA, 250-nit, 45% CG, eDP, narrow border, slim, Touch-enabled
 - (1920 x 1080) UWVA, 1000-nit, 72% CG, eDP+PSR, ultra-slim, HP Sure View
- Designed to support multiple HP docking options including HP's traditional Ultraslim mechanical dock and all-new Thunderbolt™ dock¹
- Featuring HP Collaboration Keyboard with Clickpad to manage most commonly used conferencing functions with a single keystroke
- Innovative world-facing third mic improves inbound ambient noise cancellation while 360-degree mic pick-up allows everyone to clearly hear and be heard
- Optional anti-glare touch displays with ambient light sensor
- Enterprise grade security with HP SureStart, HP Privacy Camera¹, HP Sure View⁵, HP Write Manager, SmartCard Reader¹ and Touch Fingerprint reader¹
- Optional HD camera or Infra-Red camera with multi-array microphone
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles³
- Flexible wireless connectivity options
- Pending MIL-STD 810G tests⁴

1. Sold separately or as an optional feature.

2. Not all options compatible with HP ThinPro OS.

3. HP Elite notebooks up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

4. MIL STD 810G testing is pending and is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

5. HP Sure View G3 integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape. Available in Q3' 19.

NOTE: See important legal disclosures for all listed specs in their respective features' sections

Features

PRODUCT NAME

HP mt45 Mobile Thin Client

OPERATING SYSTEM

Preinstalled

Windows 10 IoT Enterprise 2019 for Thin Clients¹
HP ThinPro/HP Smart Zero²

¹Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 IoT Enterprise automatic updates are always disabled. ISP fees may apply, and additional requirements may apply over time for updates. See <http://www.windows.com/>.

²Some features are not supported on HP ThinPro. See the respective Features sections for details.

PROCESSOR

AMD Ryzen™ 3 PRO 3300U APU with Radeon™ Vega 6 Graphics (2.1 GHz base clock, up to 3.5 GHz max boost clock, 4 MB L3 cache, 4 cores)^{2,3,4,5}

Processor Family

2nd Generation AMD® Ryzen™ PRO APU processor⁶

³Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

⁴Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.

⁵Max Boost clock frequency performance varies depending on hardware, software and overall system configuration.

⁶In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

AMD Radeon™ Vega Graphics⁷

Supports

Support HD decode, DX12, and HDMI 2.0

⁷HD content required to view HD images.

DISPLAY

Features

Non-Touch

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC (1920 x 1080)^{7, 9, 10}

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC with HD camera (1920 x 1080)^{7, 9, 10}

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC with HD + IR¹⁹ camera (1920 x 1080)^{7, 9, 10}

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC for WWAN (1920 x 1080)^{7, 9, 10}

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC with HD camera for WWAN (1920 x 1080)^{7, 9, 10}

35.6 cm (14") diagonal FHD IPS eDP anti-glare WLED-backlit slim, 250 nits, 45% NTSC with HD + IR¹⁹ camera for WWAN (1920 x 1080)^{7, 9, 10, 11}

35.6 cm (14") diagonal FHD IPS eDP + PSR anti-glare WLED-backlit ultraslim, 1000 nits with HP Sure View G3 Integrated Privacy Screen, 72% NTSC, with Ambient Light Sensor and HD+IR¹⁹ camera for WWAN (1920 x 1080)^{7, 8, 9, 10}

Touch

35.56 cm (14") diagonal FHD IPS eDP anti-glare On-Cell WLED-backlit slim touch screen, 250 nits, 45% NTSC with HD+IR camera for WWAN (1920 x 1080)^{7, 9, 10, 11}

HDMI 2.0

Supports resolution up to 4k @ 60Hz

⁷HD content required to view HD images.

⁸HP Sure View G3 integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation. Available in Q3' 19.

⁹Resolutions are dependent upon monitor capability, and resolution and color depth settings.

¹⁰Sold separately or as an optional feature.

¹¹Touch display gesture support is limited on HP ThinPro/HP Smart Zero.

Features

Displays support

Docking Station Model	Total number of supported displays (incl. the notebook display)	Max resolutions supported	Dock Connectors	Technical limitations
HP UltraSlim Docking Station	4	Dual 2.5K @ 60Hz	2xDP, 1xVGA	Dual 2.5k only with both displays into DP. Not compatible with HP ThinPro/HP Smart Zero with combo jack headset connections and RDP. USB headsets may require manual configuration of audio settings.
HP Thunderbolt Dock G2	4	Dual 2560 x 1600 @ 60Hz Single 3840 x 2160 @ 60Hz	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode	HP ThinPro/HP Smart Zero support is pending.
HP USB-C Dock G4	4	Dual 2K @ 60Hz Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	Not compatible on HP ThinPro/HP Smart Zero.
HP USB-C Dock G5	3	Dual/Single 4K @ 60 Hz (3840 x 2160) Triple 2.5K (2560 x 1600)	2xDP 1xHDMI 2.0	HP ThinPro/HP Smart Zero support is pending.
HP USB-C Universal Dock	3	Dual 4K @ 60Hz Single 5K @ 60Hz	2xDP	Not compatible on HP ThinPro/HP Smart Zero.
HP USB-C/A Universal Dock G2	3	Dual/Single 4K @ 60 Hz (3840x2160) Triple 4K @ 60 Hz (3840x2160)	2xDP 1xHDMI	HP ThinPro/HP Smart Zero support is pending.
HP USB-C Travel Dock	2	Single 2K @ 60Hz	1xHDMI, 1xVGA	Single external display. Cannot use HDMI and VGA simultaneously. HP ThinPro/HP Smart Zero may require manual configuration of display settings.
HP USB-C Mini Dock	2	Single 4K @ 30Hz	1xHDMI, 1xVGA	Single external display. Cannot use HDMI and VGA simultaneously. HP ThinPro/HP Smart Zero support is pending.

Features

STORAGE AND DRIVES

Primary M.2 Storage

128 GB SATA-3 SS TLC¹²

¹²For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

MEMORY

Memory

8 GB DDR4-2400 SDRAM (2 x 4 GB)¹³

4 GB DDR4-2400 SDRAM (1 x 4 GB)^{13,14}

Memory Slots

2 SODIMM

Both slots are customer accessible/upgradeable

DDR4 SODIMMS, system runs at 2400

Supports Dual Channel Memory

¹³Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

¹⁴4GB option only available on HP ThinPro/HP Smart Zero.

NETWORKING/COMMUNICATIONS

WLAN

Intel® Dual Band Wireless-AC 9260 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, non-vPro™¹⁵

WWAN

Intel® XMM™ 7360 LTE-Advanced Cat 9^{16,19}

NFC

NXP NPC300 Near Field Communication Module¹⁹

Miracast

Native Miracast Support^{17,19}

Ethernet

Realtek PCIe GbE Family Controller 10/100/1000¹⁸

¹⁵Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

¹⁶WWAN module requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions. eSIM is not supported.

¹⁷Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

Features

¹⁸The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

¹⁹Feature is not compatible with HP ThinPro/HP Smart Zero.

AUDIO/MULTIMEDIA

Audio

Audio by Bang & Olufsen
Integrated 3 Multi-Array Microphone
2 Integrated Stereo Speakers

Camera

720p HD camera^{7,10}
720p HD+IR camera^{7, 10, 18}

Sensors

Ambient light sensor (Select models only)
Hall Sensor

⁷HD content required to view HD images.

¹⁰Sold separately or as an optional feature.

¹⁸Internet access required.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Collaboration Keyboard spill resistant with drain¹⁹
Backlit keyboard available as an option

Pointing Devices

Clickpad with multi-touch gestures enabled, taps enabled as default
Microsoft Precision Touchpad Default Gestures Support

Function Keys

F1 - Display Switching
F2 - Blank or Privacy
F3 - Brightness Down
F4 - Brightness Up
F5 - Audio Mute
F6 - Volume Down
F7 - Volume Up
F8 - Mic Mute
F9 - Blank or Backlit Toggle
F10 - Numlk
F11 - Wireless
F12 - Calendar¹⁹

Features

Share/Present¹⁹

Call Answer¹⁹

Call End¹⁹

Hidden Function Keys

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock

Fn+E - Insert

Fn+W - Pause

¹⁹Feature is not compatible with HP ThinPro/HP Smart Zero.

Features

SOFTWARE AND SECURITY

Preinstalled Software

BIOS

HP BIOSphere Gen5²⁰
BIOS Update via Network
Master Boot Record Security
Power On Authentication
Secure Erase²¹
Absolute Persistence Module²²
Pre-boot Authentication

Software

HP Native Miracast Support^{23,19} HP Connection Optimizer
HP Hotkey Support
HP Noise Cancellation Software¹⁹
Supported protocols: Microsoft RDP; HP RGS; VMware® Horizon RDP/PCoIP, Blast Extreme; Citrix® ICA/HDX*
*Protocols are dependent on operating system installed

Manageability Features

HP Thin Update
HP Device Manager
HP BIOS Config Utility (BCU)

Client Security Software

HP Fingerprint Sensor^{24,19}
HP Power On Authentication
Windows Defender^{25,19}

Security Management

Pre-boot Authentication
TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)^{26,19}
SATA 0,1 port disablement (via BIOS)
USB enable/disable (via BIOS)
Power-on password (via BIOS)
Setup password (via BIOS)
Support for chassis padlocks and cable lock devices
HP Sure Start For AMD²⁷

¹⁹Feature is not compatible with HP ThinPro/HP Smart Zero.

²⁰ HP BIOSphere Gen5 is available on select HP Pro and Elite PCs. See product specifications for details. Features may vary depending on the platform and configurations.

²¹ For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

²² Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/> computrace-agreement. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

²³ Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

²⁴ HP Fingerprint Sensor sold separately or as an optional feature.

²⁵ Windows Defender Opt in and internet connection required for updates.

Features

²⁶Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).re TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).

²⁷HP Sure Start for AMD is available on select HP PCs with AMD processors. See product specifications for availability.

Features

POWER

Power Supply

HP Smart 45 W External AC power adapter²⁸
HP Smart 45 W External AC power adapter, 2-prong (Japan only)²⁸
HP Smart 65 W External AC power adapter²⁸
HP Smart 65 W EM External AC power adapter²⁸
45 W USB Type-C™ adapter²⁸
65 W USB Type-C™ adapter²⁸

Primary Battery

HP Long Life 3-cell, 50 Wh Li-ion^{29,30}
Support HP Fast Charge (Up to 50% in 30 minutes with 65W AC Adapter)^{29,30}

Power Cord

2-wire plug - 1.0m²⁸
3-wire plug - 1.0m²⁸
3-wire plug - 1.8m²⁸
Duckhead power cord - 1.0m²⁸
Duckhead power cord - 1.8m²⁸

²⁸Availability may vary by country.

²⁹Battery is internal and not replaceable by customer. Serviceable by warranty.

³⁰Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

WEIGHTS & DIMENSIONS

Weight

Starting at 3.37 lbs (non-touch); Starting at 3.48 lbs (touch)³¹
Starting at 1.53 kg (non-touch); Starting at 1.58 kg (touch)³¹

Product Dimensions (w x d x h)

Non- Touch

12.84 x 9.22 x 0.7 in
32.6 x 23.43 x 1.79 cm

Touch

12.84 x 9.22 x 0.71 in
32.6 x 23.43 x 1.81 cm

³¹Weight will vary by configuration.

Features

PORTS/SLOTS

Ports

- 1 USB Type-C™ (Alt Mode)
- 1 USB 3.1 Gen 1 (Charging)
- 1 HDMI 2.0³²
- 1 RJ-45 / Ethernet
- 1 Docking connector
- 1 Headphone/microphone Combo
- 1 AC power
- 1 SIM card slot¹⁶
- 1 Smartcard reader¹⁶

¹⁶Sold as an optional feature.

³²HDMI cable sold separately.

SERVICE AND SUPPORT

HP Services offers 1-year or 3-year limited warranties and 90-day software limited warranty options depending on country. Batteries have a default one-year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.³³

³³ HP Care Services are optional. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	19 V
	Average Operating Power	Windows 10
	Integrated graphics	15W
Temperature	Max Operating Power	UMA < 45W
	Operating	32° to 95° F (0° to 35° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	Operating	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random Vibration	Operating	0.75 grms
	Non-operating	1.50 grms
Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard Certifications	UL	Yes
	CSA	Yes
	FCC Compliance	Yes
	ENERGY STAR®	Yes, Select models ⁴²
	EPEAT® 2019	Yes, Registered Silver in United States ⁴³
	Australia / NZ RCM Compliance	Yes
	CCC	Yes
	Japan VCCI Compliance	Yes
	KC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	GOST	Yes
	Saudi Arabian Compliance (ICCP)	Yes
	UKRSERTCOMPUTER	Yes

³⁴Configurations of the HP mt45 Mobile Thin Client that are ENERGY STAR® certified are identified as HP mt45 Mobile Thin Client ENERGY STAR on HP websites and on <http://www.energystar.gov>.

³⁵EPEAT® 2019 registered where applicable. EPEAT® registration varies by country. See <http://www.epeat.net> for registration status by country. According to IEEE 1680.1-2018.

Technical Specifications

DISPLAYS

Panel LCD 14 inch diagonal FHD (1920 x 1080) Anti-Glare WLED UWVA 45 percent cg 250 nits eDP slim NB	Outline Dimensions (W x H)	316.17 x 197.98mm (max.)
	Active Area	309.37 x 174.02mm (typ.)
	Weight	280 g max
	Diagonal Size	14"
	Thickness	3.0mm max.
	Interface	eDP 1.2 (2 lane)
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	600:1 (typical)
	Refresh Rate	60Hz
	Brightness	250 nits
	Pixel Resolution	1920 x 1080 (FHD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	45%
	Color Depth	6 bits
	Viewing Angle	UWVA 85/85/85/85
Panel LCD 14 inch diagonal FHD (1920 x 1080) Anti-Glare WLED UWVA 45 percent cg 250 nits eDP slim Touch on Panel Narrow Bezel	Outline Dimensions (W x H)	316.112 x 197.98 mm (max)
	Active Area	309.37 x 174.02 mm (typ.)
	Weight	290 g max
	Diagonal Size	14"
	Thickness	3.0 mm (panel side) / 3.2 mm (PCBA Side) (max)
	Interface	eDP 1.2
	Surface Treatment	Anti-Glare On-cell
	Touch Enabled	Yes
	Contrast Ratio	600:1 (typ.)
	Refresh Rate	60Hz
	Brightness	250 nits
	Pixel Resolution	1920 x 1080 (FHD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	45%
	Color Depth	6 bits
	Viewing Angle	UWVA 85/85/85/85

Privacy mode, CR>2, L/R/U/D, 50/50/85/85 (typical)

STORAGE

SSD 128 GB 2280 M2 SATA-3 TLC	Form Factor	M.2 2280	
	Capacity	128 GB	
	NAND Type	TLC	
	Height	0.09 in (2.3 mm)	
	Width	0.87 in (22 mm)	
	Weight	0.02 lb (10 g)	
	Interface	ATA-8, SATA 3.0	
	Performance	Maximum Sequential Read	Performance
		Around 540 ~ 560 MB/s	Around 380 ~ 530 MB/s
	Logical Blocks	250,069,680	
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	ATA Security; DIPM; TRIM; DEVSLP		
<i>*For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 30GB is reserved for system recovery software.</i>			

Intel® 9260	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
802.11a/b/g/n/ac (2 x 2)		
Wi-Fi® and Bluetooth®		
5.1 Combo¹ Non-vPro™		
	Interoperability	Wi-Fi certified
	Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

Technical Specifications

	<ul style="list-style-type: none"> •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) •802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> •IEEE and WiFi compliant 64 / 128-bit WEP encryption for a/b/g mode only •AES-CCMP: 128 bits in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •IEEE 802.11i •WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum
Power Consumption	<ul style="list-style-type: none"> •Transmit mode: 2.0 W •Receive mode: 1.6 W •Idle mode (PSP) 180 mW (WLAN Associated) •Idle mode: 50 mW (WLAN unassociated) •Connected Standby/Modern Standby: 10mW •Radio disabled: 8 mW
Power Management	ACPI compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna Type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230: 2.8g

Technical Specifications

Operating Voltage	2. Type 126: 1.3g 3.3v +/- 9%
Temperature	Operating 14° to 158° F (~10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating Non- 0 to 10,000 ft (3,048 m) operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF LED OFF – Radio ON
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology	
Bluetooth Specification	4.0/4.1/4.2/5.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ 2.17 Mbps BLE: 1 Mbps signaling data rate ¹ 0.2 Mbps 1. Actual throughput may vary.
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Electrical Interface	USB 2.0 compliant
Bluetooth Software Supported Link Topology	Microsoft Windows Bluetooth Software
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy

Technical Specifications

LE Privacy 1.2 –Extended Scanner Filter Policies
 LE Data Packet Length Extension
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)²
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)

¹Wireless access point and Internet service is required. Availability of public wireless access point is limited.

²The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

³Check latest software/driver release for updates on supported security features.

⁴Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g(OFDM modulation).

802.11a/b/g/n/ac (2 x 2) Wireless LAN Standards Wi-Fi® and Bluetooth® 4.2 Combo¹

Interoperability

Frequency Band

Data Rates

Modulation

Security³

Network Architecture Models

Roaming

Output Power²

IEEE 802.11a
 IEEE 802.11b
 IEEE 802.11g
 IEEE 802.11n
 IEEE 802.11ac
 Wi-Fi® certified
 802.11b/g/n
 • 2.402 – 2.482 GHz
 802.11a/n
 • 4.9 – 4.95 GHz (Japan)
 • 5.15 – 5.25 GHz
 • 5.25 – 5.35 GHz
 • 5.47 – 5.725 GHz
 • 5.825 – 5.850 GHz
 • 802.11b: 1, 2, 5.5, 11 Mbps
 • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
 • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
 • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)
 • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
 Direct Sequence Spread Spectrum
 BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
 •IEEE and WiFi compliant 64 / 128-bit WEP encryption for a/b/g mode only
 •AES-CCMP: 128 bits in hardware
 •802.1x authentication
 •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
 •WPA2 certification
 •IEEE 802.11i
 •WAPI
 Ad-hoc (Peer to Peer)
 Infrastructure (Access Point Required)
 IEEE 802.11 compliant roaming between access points
 • 802.11b: +14dBm minimum
 • 802.11g: +12dBm minimum
 • 802.11a: +12dBm minimum

Technical Specifications

	<ul style="list-style-type: none"> • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode 2.0 W • Receive mode 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode 50 mW (WLAN unassociated) • Connected Standby 10mW • Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum
Antenna Type	High efficiency antenna with spatial diversity, mounted in the display enclosure
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230 : 2.3 x 22.0 x 30.0 mm
Weight	Type 2230: 2.8 g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating Non- 0 to 10,000 ft (3,048 m) operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF LED White – Radio ON
HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology	
Bluetooth Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ 2.17 Mbps BLE: 1 Mbps signaling data rate ¹ 0.2 Mbps 1. Actual throughput may vary.
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Technical Specifications

Transmit Power	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Electrical Interface	USB 2.0 compliant
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

¹Wireless access point and Internet service is required. Availability of public wireless access point is limited.

²The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

³Check latest software/driver release for updates on supported security features.

⁴Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g(OFDM modulation).

Intel® XMM™ 7360 LTE-Advanced (CAT9)¹

Technology/Operating bands	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 1400 (Band 11), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1400 (Band 21), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 2100 (Band 66).
-----------------------------------	---

Technical Specifications

	TDD LTE: 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41). HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz
Wireless protocol standards	3GPP Release 11 LTE Specification CAT.9, DL 60MHz BW throughput up to 450Mbps; UL 20MHz throughput up to 50Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
GPS	Standalone, A-GPS (MS-A, MS-B and XTRA)
GPS bands	1575.42 MHz \pm 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
Maximum data rates	LTE: 450 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
Maximum output power	LTE: 23 dBm HSPA+: 23.5 dBm
Maximum power consumption	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
Form Factor	M.2, 3042-S3 Key B
Weight	5.8 g
Dimensions (Length x Width x Thickness)	42 x 30 x 2.3 mm

Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. WWAN is an optional feature, requires factory configuration and separately purchased service contract. Check with service provider for coverage and availability in your area. 4G LTE not available on all products, in all regions.

Near Field Communications Controller (optional)	Dimensions (L x W x H)	Module 25 mm by 10 mm by 2.0 mm
	Chipset	NPC300
	System interface	I2C
	NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	NFC Forum Support	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
	Reader (PCD-VCD) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
	Card Emulation (PICC-VICC) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
	Frequency	13.56 MHz
	NFC Modes Supported	Reader/Writer, Peer-to-Peer
	Raw RF Data Rates	106, 212, 424, 848 kbps
	Operating temperature	0°C to 70°C
	Storage temperature	-20°C to 125°C

Technical Specifications

Humidity	10-90% operating 5-95% non-operating	
Supply Operating voltage	4.35 to 5.25 Volts	
I/O Voltage	1.8V or 3.3V	
Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)	Mode	Power Consumption, Typical
	Polling	710.93 mW
	Detected Test Tag Type 1	152.09 mW
	Detected Test Tag Type 2	341.26 mW
	Detected Test Tag Type 3	383.76 mW
	Detected Test Tag Type 4	312.26 mW
	Antenna	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

Technical Specifications

POWER

AC Adapter 45 Watt nPFC Wall Mount USB type C Straight 1.8m C6NS	Dimensions (H x W x D)	62.0x62.0x28.5mm	
	Weight	unit: 220g +/- 10g	
	Input	Input Efficiency	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 10V : 87.5% 12V : 87.8% 15V : 87.8% 20V : 87.8%
	Output	Input frequency range	47 to 63 Hz
		Input AC current	Max. 1.4 A at 90 Vac
		Output power	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:
		DC output	5V: 81.5%
	Connector	Hold-up time	9V: 86.7%
		Output current limit	10V: 87.5%
	Environmental Design	Non-Standard C6	
EMI and Safety Certifications	Operating temperature	Operating temperature	32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
		Altitude	0 to 16,400 ft (0 to 5,000 m)
		Humidity	20% to 95%
		Storage Humidity	10% to 95%
		*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5 mm Right Angle 1.8 m	Dimensions (H x W x D)	95.0x40.0x26.5mm	
	Weight	unit: 200g +/- 10g	
	Input	Input Efficiency	87.74% at 115Vac and 88.4% at 230Vac
	Output	Input frequency range	47 to 63 Hz
		Input AC current	Max. 1.4 A at 90 Vac
		Output power	45W
		DC output	19.5V
	Connector	Hold-up time	5 ms at 115Vac input
		Output current limit	<8.0A
		C6	

Technical Specifications

Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
	Altitude	0 to 16,400 ft (0 to 5,000 m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives	
	* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.	
	* MTBF - over 200,000 hours at 25°C ambient condition.	

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5 mm Right Angle 1.8 m 2prong	Dimensions (H x W x D)	95.0x40.0x26.5mm		
	Weight	unit: 200g +/- 10g		
	Input	Input Efficiency	87.74% at 115Vac and 88.4% at 230Vac	
		Input frequency range	47 to 63 Hz	
		Input AC current	Max. 1.4 A at 90 Vac	
	Output	Output power	45W	
		DC output	19.5V	
		Hold-up time	5 ms at 115Vac input	
		Output current limit	<8.0A	
		Connector	C6	
	Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)	
		Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)	
		Altitude	0 to 16,400 ft (0 to 5,000 m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives		
		* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.		
		* MTBF - over 200,000 hours at 25°C ambient condition.		

AC Adapter 65 Watt nPFC USB type C™ Straight 1.8 m C6NS	Dimensions (H x W x D)	74x74x28.5mm	
	Weight	unit: 245g +/- 10g	
	Input	Input Efficiency	81.5% min at 115 Vac/ 230Vac @ 5V/3A
			86.7% min at 115 Vac/ 230Vac @ 9V/3A
			88% min at 115 Vac/ 230Vac @ 10V/5A
		88% min at 115 Vac/ 230Vac @ 12V/5A	

Technical Specifications

		89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A
	Input frequency range	47 ~ 63 Hz
	Input AC current	1.7 A at 90 VAC and maximum load
Output	Output power	65W
	DC output	5V/9V/10V/12V/15V/20V
	Hold-up time	5 ms at 115 Vac input
	Output current limit	<8.0A
	Connector	Non-Standard C6
Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
	Altitude	0 to 16,400 ft (0 to 5,000 m)
	Humidity	5% to 95%
	Storage Humidity	5% to 95%
EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives	
	* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.	
	* MTBF - over 200,000 hours at 25°C ambient condition.	

Technical Specifications

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5 mm New EM	Dimensions	102x55x30mm
	Weight	unit: 250g +/- 10g
	Input	Input Efficiency 88.0 % at 115 Vac and 89.0 % at 230 Vac
		Input frequency range 47 to 63 Hz
		Input AC current Max 1.7 A at 90 Vac
	Output	Output power 65W
		DC output 19.5V
		Hold-up time 5 ms at 115 Vac input
		Output current limit <11.0A
	Connector	C6
	Environmental Design	Operating temperature 32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature -4° to 185° F (-20° to 85° C)
		Altitude 0 to 5,000 m
		Humidity 20% to 95%
		Storage Humidity 10% to 95%
	EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5 mm Right Angle 1.8 m	Dimensions	90.0 x 51 x 28.5 mm
	Weight	unit: 230 g +/- 10 g
	Input	Input Efficiency 88.0 % at 115 Vac and 89.0 % at 230Vac
		Input frequency range 47 ~ 63 Hz
		Input AC current Max 1.7 A at 90 VAC
	Output	Output power 65W
		DC output 19.5V
		Hold-up time 5 msec at 115 VAC input
		Output current limit <11.0A
	Connector	C6
	Environmental Design	4.5mm Barrel Type
		Operating temperature 32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature -4° to 185° F (-20° to 85° C)
		Altitude 0 to 16,400 ft (0 to 5,000 m)
		Humidity 20% to 95%
		Storage Humidity 10% to 95%

Technical Specifications

EMI and Safety Certifications

- *CE Mark - full compliance with LVD and EMC directives
 - * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.
 - * MTBF - over 200,000 hours at 25°C ambient condition.
-

Technical Specifications

Battery SS 3 Cell 50 WHr Long Life -PL	Dimensions (L x W x H)	L 278.7 mm x W 76.3 mm x H 7.1 mm	
	Weight	193 +/- 10g	
	Cells/Type	3cell Lithium-Ion Polymer cell / P604883A1	
	Energy	Voltage	11.55V
		Amp-hour capacity	4.113Ah/ 4.330Ah
		Watt-hour capacity	50wh
	Temperature	Operating (Charging)	0° to 50° C
		Operating (Discharging)	-10° to 60° C
	Warranty	Based on system offering, refer to http://www.hp.com/support/batterywarranty/ for battery information	
	Optional Travel Battery Available	No	

COUNTRY OF ORIGIN

China

Options and Accessories (Sold separately and availability may vary by country.)

Type	Description	Part Number
Cases	HP Essential Top Load Case	H2W17AA
	HP Essential Backpack	H1D24AA
	HP 17.3 Business Backpack	2SC67AA
	HP 15.6 Business Top Load	2SC66AA
Docking	HP UltraSlim Docking Station	D9Y32AA
	HP UltraSlim Docking Station TAA US	E5C22AV
	HP Thunderbolt Dock 120W G2	2UK37AA
	HP Thunderbolt Dock 120W G2 TAA	2UK37AA
	HP TB Dock Audio Module	3AQ21AA
	HP TB Dock 120W G2 cable	3XB94AA
	HP TB Dock G2 combo cable	3XB96AA
	HP USB-C™ Universal Dock	1MK33AA
	HP USB-C™ Dock G4	3FF69AA
	HP USB-C™ Mini Dock	1PM64AA
	HP USB Travel Dock	TOK30AA
	HP USB-C™ Universal Dock	1MK33AA
	HP USB-C™ Universal Dock w/4.5mm Adapter	2UF95AA
	HP USB-C™ Universal Dock w/4.5mm Adapter - non-flash version	3DV65AA
	HP USB-C™ Dock G5	5TW10AA
	HP USB-C™/A Universal Dock G2	5TW13AA
Input/Output	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Slim USB Keyboard and Mouse	T6T83AA
	HP Wireless (Link-5) Keyboard	T6U20AA
	HP USB Essential Keyboard and Mouse	H6L29AA
	HP Conferencing Keyboard	K8P74AA
	HP USB Collaboration Keyboard	Z9N38AA
	HP Wireless Collaboration Keyboard	Z9N39AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP X4000b Bluetooth Mouse	H3T50AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Slim Bluetooth Mouse to AMO	F3J92AA
	HP Wireless Premium Mouse	1JR31AA
	HP USB Premium Mouse	1JR32AA

Options and Accessories (Sold separately and availability may vary by country.)

HP Essential USB Mouse	2TX37AA
HP Elite Presenter Mouse	2CE30AA
HP Stereo 3.5mm Headset	T1A66AA
HP Stereo USB Headset	T1A67AA
HP UC Wireless Mono Headset	W3K08AA
HP UC Wireless Duo Headset	W3K09AA
HP USB-C™ to USB-A Hub	Z6A00AA
HP USB-C™ to DP	N9K78AA
HP USB-C™ to VGA	N9K76AA
HP HDMI to DVI	F5A28AA
HP HDMI to VGA	H4F02AA

Power

HP 65W Slim AC Adapter	H6Y82AA
HP 45W Smart AC Adapter	H6Y88AA
HP 65W Smart AC Adapter	H6Y89AA
HP 45W 2-prong 4.5 mm DC jack AC Adapter	L6F60AA
HP 45W USB-C Power Adapter	1HE07AA
HP 65W USB-C Power Adapter	1HE08AA
65W USB-C Slim Power Adapter	3PN48AA
HP Notebook Power Bank	N9F71AA

Storage

HP USB External DVDRW Drive	F2B56AA
-----------------------------	---------

Security

HP Docking Station Cable Lock	AU656AA
HP Keyed Cable Lock	T0Y14AA
HP Combination Lock	T0Y15AA
HP Essential Combination Lock	T0Y16AA
HP Keyed Cable Lock 10mm	T1A62AA
HP Dual Head Keyed Cable Lock	T1A64AA

Summary of Changes

Date of change:	Version History:	Type of change	Description of change:
July 26, 2019	From v1 to v2	Changed	Docking Section
August 21, 2019	From v2 to v3	Changed	Format page 2

© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties are contained in the limited warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Bluetooth is a trademark of its proprietor used by HP Inc. under license. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.