Product datasheet

Specifications

APC NetShelter SX, Server Rack Enclosure, 42U, Shock Packaging, 2000 lbs, Black, 1991H x 600W x 1200D mm

AR3300SP

Overview

Presentation	NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).
Lead time	

Main

Number of rack unit	42U
Provided equipment	Baying hardware Documentation CD Key(s) Leveling feet Mounting hardware Pre-installed casters Side panels User manual

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	120 cm
Net weight	134.09 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Maximum mounting depth	104.8 cm
Minimum mounting depth	19.1 cm
Rack width	19"
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Permanent permissible load	1020.58 kg dynamic 1700.97 kg static

Conformance

Standards	UL 2416
	UL 60950-1
	EIA-310E

Packing Units

Package 1 Weight	246.3 kg
Package 1 Height	217.9 cm
Package 1 width	110.5 cm
Package 1 Length	132.1 cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace