

Product datasheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord

APDU9959EU3

Overview

Lead time

Main

| | |
|-----------------------------|--|
| Main Input Voltage | 230 V |
| Main Output Voltage | 230 V |
| Input Connection Type | IEC 60309 16 A 2P + E IEC 60320 C20 |
| Number of rack unit | 0U |
| Cable length | 3.00 m |
| Number of cables | 1 |
| Communication port protocol | SNMP Redfish |
| Provided equipment | Installation guide Locking input power cord Rack mounting brackets Safety guide |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 179.4 cm |
| Width | 5.5 cm |
| Depth | 4.6 cm |
| Net weight | 5.61 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| USB compatible | No |

Input

| | |
|----------------------|-------------|
| Permissible voltage | 220...240 V |
| Max line current | 16 A |
| Input current limits | 16 A |

| | |
|-------------------|----------|
| Load capacity | 3700 VA |
| Network frequency | 50/60 Hz |

Output

| | |
|--------------------------------|-------------------------------------|
| Number of power socket outlets | 21 IEC 60320 C13 3 IEC 60320 C19 |
|--------------------------------|-------------------------------------|

Conformance

| | |
|------------------------|--|
| Product certifications | FCC part 15 class A VDE RCM EAC |
| Standards | EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | -5...60 °C |
| Relative humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0.00...15240.00 m |

Batteries & Runtime

| | |
|----------------------------|-------------------|
| Communication network type | 10/100/1000BASE-T |
|----------------------------|-------------------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 200.2 cm |
| Package 1 Width | 11.4 cm |
| Package 1 Length | 16.5 cm |
| Package 1 Weight | 8.59 kg |
| Number of Units in Package 3 | 48 |

Offer Sustainability

| | |
|-------------------|---|
| EU RoHS Directive | Under investigation |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|

Recommended replacement(s)