

LCD 23.8" Enterprise Display

Sharp MultiSync® EA241F



Re-imagine your desktop computing experience

With the MultiSync EA Series, Sharp has developed monitor solutions that push the boundaries of what you've come to know as business-class screen performance. The EA Series deliver a completely redesigned chassis with a host of enhanced features, advanced technologies, future-proof connectivity and environmentally friendly benefits. All models utilise IPS LCD panels, which boast the best possible colour accuracy and minimal viewing angle shift.

Every model features LED backlights, enabling a thin and light design. Other green features include ECO Mode™, a carbon footprint meter and an ambient light sensor, which automatically adjusts the brightness to the optimal setting depending on ambient lighting, screen content or both.

Benefits

In-demand display size – the popular 23.8" display with Full HD resolution is the perfect size for busy office workspaces.

Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

Maximum attention to health and well-being – the outstanding ergonomic height adjustment from 0 to 150 mm; eye pleasing built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to tailor the perfect individual setup to boost productivity.

Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.

Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Specifications

Product Information

Product Name

Sharp MultiSync® EA241F

Product Group

LCD 23.8" Enterprise Display

Order Code

60006212 (BK), 60006213 (WH)

Display

Panel Technology

IPS TFT with W-LED backlight

Screen Size [inch/cm]

24 / 60.47

Screen Aspect Ratio

16:9

Colour Gamuts

101.6 % sRGB; 75.3% AdobeRGB, 72% NTSC

Pixel Pitch [mm]

0.275

Brightness (typ.) [cd/m²]

250

Contrast Ratio (typ.)

1000:1 (5000:1 dynamic contrast ratio)

Viewing Angle [°]

178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

Response Time (typ.) [ms]

5 (grey-to-grey)

Colours [Mio.]

16.78 (6-bit per colour)

Synchronisation Rate

Horizontal Frequency [kHz]

31.5 - 83

Vertical Frequency [Hz]

50 - 75

Resolution

Optimum Resolution

1920 x 1080 at 60 Hz

Supported

1024 x 768;	1440 x 900;	720 x 400;
1280 x 1024;	1680 x 1050;	720 x 480;
1280 x 720;	1920 x 1080;	720 x 576;
1280 x 960;	640 x 480;	800 x 600

Connectivity

Digital

1 x DisplayPort; 1 x DVI-D (with HDCP); 1 x HDMI; USB ver. 3.1 (3 down / 1 up)

Analog

1 x D-sub 15 pin

Electrical

Power Consumption on Mode [W]

11 (Eco Mode 2); 15 (shipping); 47 (max.)

Power Savings Mode [W]

0.31

Power Supply

0.9 A/0.5 A; 100-240 V; internal power supply

Environmental Conditions

Operating Temperature [°C]

+5 to +35

Operating Humidity [%]

20 to 80

Storage Humidity [%]

10 to 85

Storage Temperature [°C]

-10 to 60

Ergonomics

Height adjustable stand [mm]

150 (Landscape mode)

Screen Tilt [°]

-5 to 35

Screen Swivel [°]
-170 to 170

Screen Rotate [°]
0 to 90 (landscape to portrait mode)

Mechanical

Bezel Width [mm]
0.8 (left/right/top); 15.8 (bottom)

Dimensions (W x H x D) [mm]
319.1 x 555.6 - 615.4 x 250 (Portrait mode); 537.7 x 336.6 - 486.6 x 250 (Landscape mode)

Weight [kg]
With stand: 6.1; Without stand: 3.6

VESA Mounting [mm]
100 x 100 (4 points)

Additional Features

Colour Versions
Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet

Cable Management
yes

Plug and Play
DDC2B/2Bi; VESA DDC/CI; VESA DDC2Bi

Audio
Integrated Speakers (1 W + 1 W)

Adjust Functions
Advanced NTAA (Advanced Non-Touch-Auto-Adjustment)

Shipping Content
Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Set-up Manual; USB Cable

Safety and Ergonomics
CE; EAC; EnergyStar 8.0; ErP; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; PSB; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA; WEEE

Warranty
3 years warranty incl. backlight; optional 1st to 3rd year 24/7 usage warranty; optional 4th to 5th year warranty extension

Green Features

Energy Efficiency
Ambient light sensor; Energy consumption: 11 kWh/1000 h; Energy efficiency class: C; Human sensor

Ecological Standards
Energy Star 8.0; ErP compliant; RoHS compliant; TCO 8.0; WEEE

* EnergyStar 8.0
* TCO 8.0



TÜV Ergonomics



RoHS



ErP



CE



TCO 8.0



TÜV GS