# Product datasheet

Specifications



## Easy PDU Metered Zero U 32A 230V (20)C13 (4)C19 IEC309

EPDU2132M

## Main

| | |
|---|---|
| **Product or component type** | PDU |
| **Main Input Voltage** | 230 V 1 phase |
| **Input current limits** | 32 A |
| **Network frequency** | 50/60 Hz |
| **Main Output Voltage** | 230 V |
| **Input Connection Type** | IEC 60309 32 A 2P + E |
| **Number of power socket outlets** | 20 IEC 60320 C13 |
| **Load capacity** | 7360 VA |
| **Max current draw** | 32 A |
| **PDU type** | Metered |
| **Number of rack unit** | 0U |
| **Number of cables** | 1 |
| **Cable length** | 2.99 m |
| **Provided equipment** | Installation guide |

## Complementary

| | |
|---|---|
| **Mounting location** | Side |
| **Mounting mode** | Rack-mounted |
| **Mounting position** | Vertical |
| **Height** | 1400 mm |
| **Width** | 56 mm |
| **Depth** | 56 mm |
| **Net weight** | 3.35 kg |

## Environmental

| | |
|---|---|
| **Product certifications** | CE<br>UKCA |
| **Relative humidity** | 5…95 % |
| **Storage Relative Humidity** | 5…95 % |
| **Ambient air temperature for storage** | -25…65 °C |
| **Operating altitude** | 0...10000 ft |
| **Ambient air temperature for operation** | -5…50 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 6.8 cm |
| **Package 1 Width** | 26 cm |
| **Package 1 Length** | 156 cm |
| **Package 1 Weight** | 4.35 kg |

## Logistical informations

| | |
|---|---|
| **Country of origin** | CN |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 24 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **806 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **48 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **9 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **2 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **740 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **7 kg CO2 eq.** |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| SCIP Number | **71fa5784-362d-425f-b9fd-61c96d223b72** |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **44** |
| End of life manual availability | End of Life Information |
| Removable battery | **No** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |

Image of product / Alternate images

**Alternative**

