



Delock DisplayPort 1.4 KVM Switch 8K 30 Hz with USB 3.0 and Audio

Description

This KVM switch by Delock is a convenient solution for connecting **four computers** with DisplayPort output to **one DisplayPort monitor**.

Additionally there is an HDMI output for connection of two monitors, of which only one can be active at a time.

Peripheral devices

Furthermore, two USB 2.0 ports for a mouse and keyboard, and **two USB 3.0 ports** for a hard drive or USB memory can be connected.

Flexible Control

The active computer can be selected by mouse gesture, keyboard hotkey, button on the device or infrared remote control.

Multi-Stream Transport (MST)

With the support of MST (Multi-Stream Transport), **multiple monitors** can be used at the DisplayPort output **with an optional MST hub**.

Note

KVMs emulate a standard wired 104 key keyboard and wired generic 2 or 3 button scroll wheel mouse on their respective console ports. Whether or not a wireless or gaming mouse and keyboard work with KVM switches depends on several factors; in general, most wireless mice and keyboards do not support working with KVM switches. We recommend to use a standard wired mouse and keyboard with our KVM switches.

Specification

| Connectors: Input: 4 x DisplayPort female 4 x USB 3.0 Type-B female 8 x 3.5 mm 3 pin stereo jack female (audio) 1 x 3.5 mm 3 pin stereo jack female for optional IR-receiver 1 x DC 5 V power connector screwable Output: 1 x DisplayPort female 1 x HDMI-A female 2 x USB 3.0 Type-A female (USB 3.0 Hub) 2 x USB 2.0 Type-A female (keyboard + mouse) 4 x 3.5 mm 3 pin stereo jack female (audio) Switching via button, mouse button, hotkey or infrared remote control Automatic switching when turning a PC on or off Supports HDCP 1.4 and 2.2 Supports MDT (Multi-Stream Transport) |
|--|
| |
| |
| |
| |
| o |
| |
| |
| ••• |
| |
| Resolution up to: |
| DisplayPort output: |
| 7680 x 4320 @ 30 Hz |
| 3840 x 2160 @ 60 Hz |
| |
| 3840 x 2160 @ 60 Hz |
| (depending on the system and the connected hardware) |
| Robust metal housing Calcure black |
| • Colour: black |
| Dimensions (LxWxH): ca. 243 x 75 x 26 mm |



ltem no. 11484

EAN: 4043619114849

Country of origin: China

Package: • Retail Box





Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 5 V / 3 A
- · Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm

System requirements

- PC with DisplayPort female + USB Type-A female
- Monitor or TV with DisplayPort or HDMI interface
- Connection cables

Package content

- KVM switch with USB and audio
- Remote control
- 4 x cable USB 3.0 A male to USB 3.0 B male, length ca. 1.0 m
- External power supply
- Mounting brackets and screws
- User manual

Images







| Interface | |
|----------------------------|---|
| Output: | 1 x DisplayPort 20 pin female |
| | 1 x HDMI-A 19 pin female |
| | 2 x USB 3.0 Type-A female |
| | 2 x USB 2.0 Type-A female |
| | 4 x 3,5 mm Klinkenbuchse (Lautsprecher, Mikrofon) |
| Input: | 1 x 5 V DC female 5,5 mm x 2,1 mm |
| | 2 x DisplayPort 20 pin female |
| | 4 x 3.5 mm stereo jack female (speaker, microphone) |
| | 2 x USB 3.0 Type-B female |
| Technical characteristics | |
| Maximum screen resolution: | 7680 x 4320 @ 30 Hz |
| Physical characteristics | |
| Housing colour: | black |
| Housing material: | metal |
| Length: | 178.0 mm |
| Width: | 75 mm |
| Height: | 26 mm |