



1594L 15.6-inch LCD

Open-Frame Touchscreen



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1594L 15.6-inch FHD open-frame LCD touchscreen delivers a sleek, compact design with Elo's industry-leading TouchPro PCAP technology seamlessly integrated - providing stable performance, crystal-clear image quality, and optimal light transmission for precise touch interactions. With its captivating display, the Elo 1594L is well suited for integration into self-service and HMI applications in retail stores, restaurants, gaming and casinos, amusement parks, industrial automation and more.

Video Interfaces: HDMI, VGA & Display Port

Elo's TouchPro PCAP offers:

- **2GS (two glass solution) with pristine optical clarity and touch durability.**
- **10 touch with thru-glass capabilities that passes UL-60950 & IK-07 impact testing**

Compatible with the Elo Backpack - a low-power, solid-state, fan-less computing solution

1594L 15.6-inch Open-Frame Touchscreen

Specifications	
Model	1594L
Color	Black
Active Display Area	13.55" x 7.62" / 344.16 mm x 193.59 mm
Diagonal	15.6"
Aspect Ratio	16:9
Dimensions	15.54" x 9.53" x 1.71" / 394.7mm x 242.0mm x 43.4mm
Native Resolution	1920 x 1080
Other Supported Resolutions	640 x 480 60Hz; 720 x 400 70Hz; 800 x 500 60Hz; 800 x 600 56, 60Hz; 1024 x 768 60Hz; 1280 x 800 60Hz; 1280 x 1024 60Hz; 1440 x 900 60Hz, 60Hz RB; 1680 x 1050 60Hz, 60Hz RB; 1920 x 1080 50 60Hz
Number of Colors	16.7 million
Number of Touches	10-touch
Brightness (typical)	LCD Panel: 350 nits; TouchPro PCAP: 315 nits
Response (typical)	25 msec
Viewing Angle	Horizontal: 89°/178°; Vertical: 89°/178°
Contrast Ratio	800:1
On-Screen Display	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of Display Port video input Input Video Horizontal Sync frequency range: 30 - 82KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth) Monitor input power signal specifications: 12VDC +/- 5% Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) barrel length)
Power Consumption	ON (monitor + power brick): 13.23W SLEEP (monitor + power brick): 0.48W OFF (monitor + power brick): 0.22W
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Weight	Unpackaged: 6.7 lbs / 3.02 kg; Packaged: 10.2 lbs / 4.62 kg
Shipping Dimensions	18.5" x 13.03" x 6.89" / 470mm x 331mm x 175mm
Mounting Options	75mm VESA mount; 2-hole mounting interface on all 4 sides; Rear mount; Flush mount with included brackets
Warranty	3 years standard
MTBF	50,000 hours demonstrated
Agency Approvals	UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; EAC; RoHS, China RoHS, WEEE
Compliance	GLI 15 kV air / 8 kV contact ESD compliant UL62368 ball-drop compliant IK07 impact compliant
What's in the Box	HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, Quick Install Guide; Flush Mount Brackets w/Screws, EEI Label, Japan Class-B TM info sheet

Ordering Information

Part Number	Part Description	Technology	Interface	Surface Treatment	Video Interface	Availability
E131375	ET1594L-2UWB-0-MT-ZB-NPB-G	TouchPro PCAP	USB 2.0	Clear	HDMI, VGA & Display Port	Worldwide

Extended Warranty Options

Part Number	Description
E898247	4 Year Warranty Coverage
E898449	5 Year Warranty Coverage
E898648	3 Year Warranty Coverage + AUR
E894921	4 Year Warranty Coverage + AUR
E895125	5 Year Warranty Coverage + AUR

Learn more about Elo at EloTouch.com.

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2023 Elo Touch Solutions, Inc. All rights reserved. 23092AES00176

