

ASUS SimPro Dock 2

Peripheral Series



Specification

Model Name	ASUS SimPro Dock 2
I/O Port - Front Panel	1 x Audio Combo Jack(Headphone jack and headset with microphone) 1 x Thunderbolt 3 USB-C for ultrafast up to 40 Gbps speeds, fast charging and video output 1 x USB 3.2 Gen 2 Type-C (Data Transfer,Power Delivery) 1 x USB 3.2 Gen 2 Type-A supports fast charging 1 x USB 3.2 Gen 2 Type-A 1 x Smart Card Reader 1 x Power Button and Status Indicator for NB(Supported ASUS NB model only)
I/O Port - Rear Panel	1 x USB 3.2 Gen 1 Type-A 1 x Display Port 1.4 with audio, resolution to 7680x4320 @ 30Hz 1 x Display Port 1.4 with audio, resolution to 3840x2160 @ 60Hz 1 x HDMI 2.0 (up to 3840 x 2160 @ 60Hz) 1 x VGA (640×480(4:3) / 800×600 (4:3) / 1024×768 (4:3) / 1280×1024 (5:4) / 1600×1200 (4:3) / 1920×1200 (16:10) /1920*1080(16:9)) 1x RJ45 Gigabit Ethernet with MAC address pass-through, remote port-disablement and Wake-on-LAN 1 x Kensington Lock slot 1 x DC Jack(6 phi) 1 x Thunderbolt 3 Cable link to NB(system) with Charging function(Length: 60cm)
Characteristics	Automatically copy MAC address from laptop to docking Power button to turn on/off laptop LED light to sync laptop power status Up to 120W for compatible laptops
Adapter	180 Watt adapter(6 phi)–ASUS proprietary
Dimension	40.6mm x 99mm x 161.5mm
Weight	640g