Eaton EVBAF332X

Catalog Number: EVBAF332X

Eaton Basic G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 42 outlets (24)C13, (18)C39

1730 mm

Ukr

General specifications

24xC13,18xC39

Product Name Catalog Number Eaton Rack PDU G4 EVBAF332X

Model Code **EAN**

PDU G4 BA 0U 309 32A 3P 3553340697166

Product Length/Depth

Product Height Product Width

53 mm 52 mm

Product Weight Warranty 4.9 kg 3 year

Compliances Certifications

СВ IEC 62368-1 LVD Directive EN IEC 63000

RoHS Directive CE WEEE Directive EAC **Packaging Directive UKCA** Cm







Product specifications

Electrical connection

Connecting cord with plug

Wattage

22 kW max

Form factor

0U (Vertical)

Mounting direction

Vertical

Number of Outputs 6-20R

0

Number of Outputs C20

0

Amperage Rating

32 A

Input connection

IEC-60309 32A 3Ph

Num of Outputs PC (SCHUKO)

0

Number of Outputs L14-30R

0

Fitted with:

Mounting material

Frequency rating

50/60 Hz

Evaluation

Other

Operating Temperature

0° to 60°C (32° to 140°F)

Number of outlets with earth pin

42

No of Outlet Suisse Stndrd Type25

0

Circuit breaker

(6) single-pole

Mass configuration

Resources

Brochures

Rack PDU G4 Brochure EN

Declarations of conformity

EU declaration of conformity Rack PDU G4

No of Outlet Suisse Stndrd Type23

0

Special features

Versatile C39 outlet
supports C14 or C20 power
cord plug
High retention outlets
designed to securely fit
standard power cords and
support P-Lock power cords
Color-coded outlet banks
and corresponding circuit
breakers

Cord length

3m

Number of Outputs 6-15R

0

Color

Black

SNMP

No

Over voltage category

2

Outlets

(24) C13, (18) C40

Number of Outputs L6-30R

0

Number of Outputs 5-20R

0

Number of UK BS1363 sockets

0

Number of Outputs 5-15R

0

Number of Outputs L5-30R

0

No of Outlet Suisse Stndrd Type15

0

Number of Outputs C13 24
No of Outlet Suisse Stndrd Type13 0
Phase Three-phase
Mounting dimension (standardized) Metric
Accessories
Rack PDU Rack mounting accessories Quickstart guide Safety Instructions
Number of outputs hardwired 0
Number of outputs (other) 18
Ethernet interface No
Communication No
Number of Outputs C19 18
Outlet control No
Switchable No
Input voltage 240/415V
Material Aluminium
Number of Outputs L6-20R
Series G4
Type Basic Rack PDU

Amperemeter

No

Serial interface

No

Mounting Dimension (metrical)

52

Number of Outputs L5-20R

0



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia