

# CITIZEN

Modern, high performance, top-exit  
printing

Safer. Cleaner. Printers.



### Self-protective housing and disinfectant ready

The CT-E301 was not only designed to withstand the harsh chemicals of disinfection products but to stop bacteria in it's tracks too. The technology within the casing and the printer itself has an SIAA mark fulfilling ISO 22196 which further reinforces that it is engineered to deliver effective results against bacteria growth and are designed to the highest industry standards.

### Future-proof interface options

The CT-E301 is available in two interface configurations – standard USB or triple interface including USB, Serial and Ethernet. So, no matter what POS system you have in place you'll be able to connect.

### Modern, compact design

Designed to have one of the smallest footprints on the market, the CT-E301 is perfect for environments where space is scarce. Easily fit it alongside a cash drawer, integrate it into a kiosk or simply have it displayed on the counter with a scanner.

## CT-E301

POS, Receipt printer (thermal 3 inch / 80mm)

### Applications

- Hospitality
- Retail
- Healthcare
- Journal
- Kiosk
- Kitchen
- Pharmacy
- Queue Management



TOMORROW'S PRINTING TODAY

# CITIZEN

## Specifications

Model	CT-E301
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	250 mm/sec.
Print Width (maximum)	72 mm
Media Width (min to max)	57.5 - 79.5 (+/- 0.5 mm)
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	53 to 85 µm
Main Interface	Triple interface: Serial, USB and Ethernet
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Control panel	1 button, 2 LEDs
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	8MB
Size (W x D x H) and Weight	108 x 125 x 165 mm, 1.3Kg
Cutter	Guillotine type, full and partial
EMC and safety standards	CE, C-UL, VCCI, FCC class A, UL, CCC

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

## CT-E301

**POS, Receipt printer (thermal 3 inch / 80mm)**

### Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Quick and easy media changing - drop-in paper loading
- Printing Speed: Fast print out of receipts - up to 250mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- Small footprint
- Tool-free maintenance



Modern, compact and efficient