


Key **Features**

- Fogra Certified
- Delta E<2 colour accuracy
- Hardware colour calibration
- KVM Switch technology with USB Type-C
- Versatile Connectivity supports Daisy Chain



Product **Description**

Recognised by Fogra as a Class A FograCert Softproof monitor, one of the highest visual quality standards, ViewSonic's VP2785-2K achieves rich visual quality and ensures the photo or design you are working on will be colour accurate and consistent on your final output. Covering 100% of the Adobe RGB colour space and 96% DCI-P3, the ViewSonic VP2785-2K QHD monitor meets the high colour standards of filmmakers, video editors, animators, print departments, illustrators, photographers, and other design professionals. It features future-proof DisplayPort technology, as well as HDMI and USB 3.1 Type-C ports. You can also daisy chain monitors from the Type-C or DP ports. To ensure precise, uniform colour, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior colour accuracy. An integrated colour uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colours. What's more, productivity-boosting features include an advanced ergonomic design, a built-in ambient light and presence sensor, and a KVM switch.



- 1. Menu Controls
- VESA Compatible (Wall Mount 100x100mm)
- 3. USB Downstream (Type-C, 5V/3A) 4. USB Downstream (Type-A, 5V/0.9A) 5. USB Upstream (Type-B)
- USB 3.1 Type-C (DP Alt mode, 60W Power delivery)
 HDMI
- 8. Display Port (Input)
- Display Port (Output/MST daisy chain)
 Audio Out
 DI

Visit Us — www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	15 ~ 130KHz
Viewable Area (in.):	27	Frequency Vertical:	24 ~ 120Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	2560 x 1440	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet -
Resolution Type:	QHD	Digital Gyno.	Type C
Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	
Dynamic Contrast Ratio:	20M:1	Height Adjust (mm):	130
Light Source:	LED	Swivel:	120°
Brightness:	300 cd/m2 (typ)	Tilt (Forward/Back):	-5° / 21°
Colours:	1.07B	Pivot (Right/Left):	90° / 90°
Colour Space Support:	10 bit (8 bit + A-FRC)	WEIGHT (METRIC)	
Aspect Ratio:	16:9	Net (kg):	6.7
Response Time (Typical GTG):	5ms	Net Without Stand (kg):	4.1
Viewing Angles:	178º horizontal, 178º vertical	Gross (kg):	10.2
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (METRIC) (WXI	HXD)
Curvature:	Flat	Packaging (mm):	720 x 460 x 268
Refresh Rate (Hz):	60	Physical (mm):	612 x 545 x 215
Blue Light Filter:	Yes	Physical Without Stand (mm):	612 x 363 x 57
Flicker-Free:	Yes	GENERAL	
Colour Gamut:	Adobe RGB: 114% size / 100% coverage (Typ) EBU: 152% size / 100% coverage (Typ) REC709: 154% size / 100% coverage (Typ)	Regulations:	cTUVus, FCC-B, ICES003, CEC, NRCan, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, BSMI, RCM, CCC, China RoHS, China Energy Label
	SMPTE-C: 166% size / 100% coverage (Typ) NTSC: 109% size (Typ) sRGB: 154% size / 100% coverage (Typ)	PACKAGE CONTENTS:	VP2785-2K x1, 3-pin Mickey Mouse Plug (IEC C5) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB3.1 Up Stream Cable(cable length :1.8M), AC/DC Adapter x1, Quick Start Guide x1
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Daniela/Diagraph	Please dispose of in accordance with
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Recycle/Disposal:	local, state or federal laws.
COMPATIBILITY		Warranty:	*Warranty offered may differ from market to market
PC Resolution (max):	2560x1440		market to market
Mac® Resolution (max):	2560x1440		
PC Operating System:	Windows 7/8/8.1/10 certified; macOS tested		
Mac® Resolution (min):	2560x1440		
USB 3.1 Type A:	3		
USB 3.1 Type B:	1		
USB 3.1 Type C:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
Display Port:	1		
Display Port Out:	1		
Power in:	External power adapter		
POWER			
Eco Mode (Conserve):	29.85W		
Eco Mode (Optimised):	34.71W		
Consumption (typical):	40.46W		
Consumption (max):	52.98W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	External		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organisation:	Yes		
CONTROLS			
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		

Copyright © ViewSonic Corporation 2000-2020. All rights reserved.