

## USB 3.0 Active Extension Cable Pro, 15m

Part No.: 43229



### Description

- Add an additional 15m to your USB 3.0 Active Extension System Pro
- Supports USB 3.0/USB 3.1 Gen 1 SuperSpeed transfer rates of up to 5Gbps
- Plug & Play and backwards compatible with both USB 2.0 and USB 1.1 devices
- Latching Type A port for secure connection
- 2 year warranty

This cable is designed to be used as the starting point in an installation using the LINDY USB 3.0 Active Extension System Pro ([43157](#), [43158](#) and [43159](#)) which gives you access to USB 3.0 SuperSpeed peripherals at long distances.

If you use 43229 together with the LINDY USB 3.0 Active Extension System Pro the first segment can be either 43229 or 43158!

Up to three of these cables from this range of products can be connected to create a USB 3.0 connection spanning up to 40m. A USB hub can be provided as the final segment by connecting a LINDY 10m USB 3.0 Active Extension Pro 4 Port Hub, allowing multiple devices to be connected.

The 15m USB 3.0 Active Extension Cable Pro is powered by your computers USB interface and includes a separate USB power cable which can be connected to provide additional power when used in conjunction with USB peripherals with high power requirements or when multiple cables are cascaded together.

For added convenience the Extension cable features a latching type connector that allows a secure connection to be made between it and other cables from the LINDY USB 3.0 Active Extension System Pro.

### Installation Examples:

- Computer > 43229 (15m) > USB Device
- Computer > 43229 (15m) > 43157 (10m) with power supply > USB Device
- Computer > 43229 (15m) > 43159 (10m) with power supply > Up to 4 USB Devices
- Computer > 43229 (15m) > 43229 (15m) with power supply > USB Device
- Computer > 43229 (15m) > 43229 (15m) > 43157 (10m) with power supply > USB Device

### Package Contents:

15m USB 3.0 Active Extension Cable Pro  
USB A Male to 2.5/0.7mm DC Cable, 1.5m  
LINDY Manual

### Technical details

- USB 3.0 / USB 3.1 Gen 1 SuperSpeed 5Gbps Interface
- USB 3.0 Type A Male to Type A Female (with latch for use with the LINDY USB 3.0 Active Extension System Pro cables)

- Chipset: VL210 & VL811
- Length: 15m
- Dimensions:
  - Type A Female connector housing: 8x2x1.3cm
  - Mid Repeater housing: 8.5 x 1.2cm (diameter)
- DC Connector Size: 2.5/0.7mm
- Operating Temperature: 0°C – 50°C
- Storage Temperature: -40°C – 55°C

© LINDY 2017