

Fujitsu recommends Windows 11 Pro.

Data Sheet

Fujitsu Tablet STYLISTIC Q7312

Tablet Mobility Meets Notebook Productivity

The Fujitsu Tablet STYLISTIC Q7312 is a highly durable and secure 2-in-1 detachable that meets the demands of today's mobile professionals. Its 33.8 cm (13.3-inch) FHD anti-glare display comes with pen and touch support. The latest 12th generation Intel® Core™ i7 vPro® processor technology and Intel® Thunderbolt™ 4 ensure excellent performance, even when you're on the go.

Combined tablet mobility and notebook productivity in one device - wherever you are. The robust IP42 compliant housing with reinforced corners and port caps protects your device from damages, even outside the office.

- Highly durable IP42 compliant housing with reinforced corners
- Port caps that protect the interfaces like the new Intel® Thunderbolt™ 4 from water spills
- Optional backlit keyboard dock with LAN and charging port
- Optional TPU cover for more robustness
- Always connected and instantly ready

Convenience at work

Sign documents legally secure. The pen is automatically charged within seconds when stored in its pen garage, that protects it also from being lost. Ready whenever you need it.

- 33.8 cm (13.3-inch) Full HD anti-glare touch display
- Supporting pen with 4K pressure levels
- Pen garage with inductive charging function

Lean, agile and secure

More freedom to work safely from anywhere at anytime without compromises in security and data protection – integrated IR Cam with Windows Hello support, fingerprint sensor and Smartcard reader protect your device like a mansion.

- Weight starting at 789 grams, the device offers you ultimate portability
- Fingerprint sensor & IR Camera supporting Windows Hello
- Smartcard reader
- Kensington lock support
- Up to 10 hours battery runtime
- Intel® Iris® Xe Graphics



Components

| | |
|---|--|
| Base unit | STYLISTIC Q7312 |
| Operating systems | |
| Operating system pre-installed | Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home |
| Operating system compatible | Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home |
| Operating system notes | Internet connectivity Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com . |
| Processor | Intel® Core™ i7-1265U processor (10 Cores, up to 4.8 GHz) |
| | Intel® Core™ i5-1245U processor (10 Cores, up to 4.4 GHz) |
| | Intel® Core™ i5-1235U processor (10 Cores, up to 4.4 GHz) * |
| | Intel® Core™ i3-1215U processor (up to 4.4 GHz) * |
| | *Processor only for retail, SMB, education and government |
| Hard disk drives (internal) | PCIe-SSD, 512 GB M.2 NVMe module, SED |
| | PCIe-SSD, 256 GB M.2 NVMe module, SED |
| | PCIe-SSD, 1 TB M.2 NVMe module, SED |
| Hard disk notes | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery |
| Interface add on cards/components (optional) | |
| 4G/ LTE (optional) | Quectel EM120R-GL (4G Cat.12) (Downlink speed 600 MB/s, Uplink speed 150 MB/s) |
| Display | 33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1,080 pixel, Anti-glare touchscreen, 400 cd/m ² , 1500:1 |
| Multimedia | |
| Camera | Front: HD Cam (0.9MP) with LED Front: IR Cam (0.9MP) supporting Windows Hello with LED Rear: 5M with LED |

Base unit

| | |
|-----------------------------------|---|
| Base unit | STYLISTIC Q7312 |
| General system information | |
| Chipset | Integrated in CPU |
| Supported capacity RAM (min.) | 8 GB |
| Supported capacity RAM (max.) | 32 GB |
| Memory slots | LPDDR4 (4266 MHz) |
| Memory notes | 8 GB / 16 GB / 32 GB onboard Dual channel support LPDDR4x (4,266 MHz) |
| LAN notes | Virtual MAC address. LAN connector via optional keyboard docking or optional USB to LAN adapter |
| Integrated WLAN | Intel Wi-Fi 6E AX211 - WLAN, BT, SRD cat. 2 |
| BIOS version | UEFI Specification 2.8 |

General system information

| | |
|-------------------------|--|
| BIOS features | InsydeH2O BIOS |
| Audio type | On board |
| Audio codec | Realtek ALC257 |
| Audio features | 2x digital array microphones, 2x built-in speakers (stereo) |
| Waterproof / Spillproof | IP42 |
| Disinfectable | no |
| MIL-STD tested | Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty. |

Display

| | |
|-------------------------------|---|
| Diagonal Size | 33.8 cm (13.3-inch) |
| Display Technology | IPS |
| Display type | Anti-glare touchscreen |
| Display Resolution type | FHD |
| Display Resolution type | Full HD |
| Resolution (native) | 1,920 x 1,080 pixel |
| Brightness - typical | 400 cd/m ² |
| Contrast - typical | 1500:1 |
| Viewing angle (h/v) - typical | 178°/178° |
| Display notes | Wide-view high-bright LED display (for enhanced outdoor viewing) Integrated ambient light sensor for automatic backlight adjustment to the working environment. Toughened glass |
| Sensors | Ambient Light Sensor Compass Gyroscope Proximity |
| Digitizer / Touch Technology | Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen |
| Pen | AES 4k pressure level Pen garage inductive charging |
| Ambient light sensor | Integrated |
| Ambient light sensor notes | While enabled, the ambient light sensor automatically adjusts the display backlight |

Graphics

| | |
|-----------------------|--|
| Base unit | STYLISTIC Q7312 |
| TFT resolution (HDMI) | up to 4,096 x 2,160 @ 60 Hz |
| Graphics brand name | Intel® Iris® Xe Graphics (with Dual channel memory) |
| Graphics features | 4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5 |
| Graphics notes | Shared memory depending on main memory size and operating system 3D accelerator |

Interfaces

| | |
|------------------------------|--|
| DC-in | 1 |
| Audio: line-out / headphone | 1 (combo port with Audio line-in) |
| Audio: line-in / microphone | 1 (combo port with Audio line-out) |
| Internal microphones | 2x digital array microphones |
| USB 2.0 total | 1 |
| USB 3.2 Gen1 (5 Gbps) total | 1 x Type-A |
| USB 4.0 Gen3 (20 Gbps) total | 1 x Type-C Intel® Thunderbolt™ 4 (with Power Delivery functionality) |
| USB Type-C | 1 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W) |
| Thunderbolt™ 4 total | 1 |
| HDMI | 1 v1.4 |

Interfaces

| | |
|---------------------------------------|--|
| Ethernet (RJ-45) | - |
| Memory card slots | 1 (USH-I) SD 3.0 Standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB |
| SmartCard slot | optional |
| SIM card slot | 1 (Nano-SIM, only for models with integrated 4G/LTE module) |
| eSIM card | supported |
| Interface Module notes | LAN and VGA available via conversion cable., Ethernet via conversion cable (USB to RJ-45) |
| Docking connector for Port Replicator | 1 |
| Kensington Lock support | 1 |

Port Replicator interfaces (optional)

| | |
|-------------------------|---|
| | USB Type-C PR |
| DC-in | 1 (19V/90W required) |
| Power on switch | 1 |
| Audio: comments | 1 Combo jack for headset usage |
| DisplayPort | 1x V1.2 |
| VGA | 1 |
| HDMI text | 1 |
| Interface Notes | 3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input |
| Kensington Lock support | no |
| Ethernet (RJ-45) | 1 |
| Notes | Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client. |

Wireless technologies

| | |
|-----------------|--|
| Antennas | 2x dual band for WLAN, 2x for LTE, Bluetooth shared with WLAN |
| Bluetooth | V5.2 |
| Integrated WLAN | Intel Wi-Fi 6E AX211 - WLAN, BT, SRD cat. 2 |
| WLAN encryption | WPA/WPA2/WPA3 (Wi-Fi Protected Access) |
| WLAN notes | Import and usage according to country-specific regulations. |
| Integrated WWAN | LTE Quectel EM120R-GL (Cat 12) - LTE |
| WWAN notes | Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE) |
| GPS | Embedded in 4G module if configured with WWAN |

Power supply

| | |
|-----------------------|--|
| AC adapter | 19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C |
| Notes | 65W AC Adapter for usage with system |
| Rated voltage range | 100 V - 240 V (AC Input) |
| Rated frequency range | 50 Hz - 60 Hz |
| 1st battery | Li-Ion battery 3-cell, 38 Wh, 38 Wh |
| Battery features | Quick Charge: 80% in 1h |
| Runtime 1st battery | 10,5 h |
| Battery notes | Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. |

Dimensions / Weight / Environmental

| | |
|-------------------------------|---|
| Dimensions (W x D x H) | 315 x 200.9 x 10.5 mm 12.4 x 0.79 x 0.42 inch |
| Weight | from 0.800 kg slate only, weight of keyboard docking from 0.465 kg |
| Weight (lbs) | from 1.75 lbs slate only , weight of keyboard docking from 1.25 lbs |
| Weight notes | Weight may vary depending on actual configuration |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F) |
| Operating relative humidity | Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity) |
| Product | STYLISTIC Q7312 |
| Germany | GS (planned) |
| Europe | CE CB |
| USA/Canada | FCC (depending on configuration) |
| Global | TCO Certified 8.0 in progress EPEAT® Silver (dedicated regions) (planned) Microsoft Operating Systems (HCT / HCL entry / WHQL) MIL-STD-810H tested RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

Additional Software

| | |
|------------------------------------|---|
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software) |
| Additional software (notes) | Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. |

Manageability

| | |
|--------------------------|---|
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 14.0 (depending on processor) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | Inventory Management BIOS Management Driver Management Security Management Alarm Management |

Manageability

| | |
|---------------------|--|
| Supported standards | WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) WBEM (Web Based Enterprise Management) BootP (made4you) |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Security

| | |
|--------------------------|---|
| Physical Security | Kensington Lock support |
| System and BIOS Security | Absolute Persistence® technology capable BIOS EraseDisk Trusted Platform Module (TPM 2.0) |
| User Security | Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Smartcard reader (optional) SystemLock BIOS SmartCard security AuthConductor Client Basic (secure authentication solution) |
| Security Notes | The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation. |
| Packaging information | |

Warranty

| | |
|-----------------------------|--|
| Warranty period | 2 years (for countries within EMEA) |
| Warranty type | Bring-in Service / Collect & Return Service (depending on country) |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Digital bug fixes | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. |

Product Support - the perfect extension

| | |
|--------------------------|---|
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | at least 5 years after shipment, for details see https://support.ts.fujitsu.com/ |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

Recommended Accessories

Thunderbolt™ 4 Port Replicator



First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®).
The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.

Order Code:
FPCPR401BP

USB Type-C AC Adapter



Recharge your notebook or tablet at work, at home or on the road with this USB Type-C power source easily.

Order Code:
S26391-F3326-L502

Tablet Stand for STYLISTIC Q devices



The tablet stand is designed for STYLISTIC devices like latest STYLISTIC Q7312 and can be used universally. Fits for STYLISTIC Q5 and Q7 and the Type-C as well as the Thunderbolt™ 4 port replicator can be fixed on the stand.

Order Code:
FPCSK769BP

AES Pen



Take your creativity to the next level, with the most natural pen experience with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen. The pen fits in the device's integrated pen garage.

Order Code:
S26391-F3389-L500

Bumper Case Kit



The protective bumper case kit is designed to prevent damages to your STYLISTIC Q7. Openings of the cover allow you to access all ports and buttons whilst the hand strap on the back of the case gives you a firm grip while working with your tablet outside the office. The integrated stand solution enhances your productivity.

Order Code:
S26391-F3396-L200

Folio Cover STYLISTIC Q7311/ Q7310



The Folio Cover for the STYLISTIC Q7311 and Q7310 is a thin, tailored protective sleeve for your Fujitsu tablet. It keeps the device safe from damage on the go, and brings a touch of style to your daily work. It can even be used as a stand if you need to display a presentation or watch a clip and fits even the device is connected to its keyboard dock. Inclination stand style 120 to 150 degree

Order Code:
S26391-F3509-L100

Order Code:
FPCKG453BP

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet STYLISTIC Q7312, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet STYLISTIC Q7312, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.
Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2022-11-22 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2022 Fujitsu Technology Solutions GmbH