



Kindermann PD-50 Series

Everything you need. Zero obstacles.

The Kindermann PD-50xx Professional Display has been uncompromisingly developed for applications where reliability, security, and seamless integration are essential.

Without an integrated operating system, but equipped with robust industrial hardware and professional connectivity, the PD-50xx is the ideal platform for digital signage, education, corporate communication, and security-critical environments. With 550 cd/m² brightness, USB-C with charging functionality, and OPS integration, it offers maximum flexibility for integrators, resellers, and IT departments.

Top selling points, User benefits and key specifications

- > **Reliable 24/7 operation**
Built for continuous professional use, the PD-50xx combines a durable full-metal housing with true 24/7 capability. The result: maximum reliability and long-term performance in demanding environments.
- > **Secure and fully controlled – no operating system**
With no integrated OS, there are no software dependencies, forced updates, or added security risks. Integrators and IT teams maintain full control over all deployed systems and players.
- > **Ready in seconds – no boot time**
Operating without an OS means no waiting. From energy-saving standby, the display is ready within seconds – ideal for efficient setups with high availability.
- > **Flexible integration with OPS slot**
The integrated OPS slot allows seamless integration of a PC module directly into the display. Solutions can be deployed cleanly, space-efficiently, and without additional hardware.
- > **Modern, future-ready connectivity with USB-C**
The USB-C video input with power delivery connects modern devices using a single cable. Video and power are transmitted simultaneously – simple, efficient, and built for the future.
- > **Clear visibility in any environment**
With 550 cd/m² brightness and a 25% haze anti-glare surface, content stays clearly visible even in challenging lighting conditions – ensuring consistent readability and image clarity.
- > **Works best with: Kindermann Klick&Show**
Transform the PD-50xx into a wireless presentation solution. With Klick&Show, content can be shared easily, quickly, and without software installation from any device.



GET IN TOUCH!



More Information
Visit our product website



Contact us
and request your launch package or demo unit.

Use cases



Ideal for installations in educational institutions, corporate environments, government facilities, as well as retail and public spaces.



Flexible installation options

Portrait mode and a tilt of up to 30° enable versatile and creative installations. Ideal for signage, information points, menu boards, and custom display solutions across a wide range of applications.



Price overview

Modell	SKU	MSRP*
PD-5055 (55")	3070000001	709,-
PD-5065 (65")	3070000002	999,-
PD-5075 (75")	3070000003	1.419,-
PD-5086 (86")	3070000004	1.949,-
PD-5098 (98")	3070000005	3.949,-

Key-Features

Feature	PD-55 Series
Diagonal in inches	55", 65", 75", 86", 98"
Native resolution (pixels)	3840 x 2160 px
Brightness	>550 cd/m ²
Connections	1x USB-C for video-, audio-signal charging function up to 15W, 2x HDMI in, 1x DP in, 1x OPS slot 18V/5A, 1x VGA (1920x1080@60Hz), audio output (3.5 mm), mic-in (3.5 mm), 1x LAN 10/100 Mbit/s, RS232 RJ45 in/out

Accessoires

Artikel	SKU	MSRP*
Klick&Show K-FleX	7488000361	795,-
Klick&Show K-FX Plus	7488000362	1.295,-
Klick&Show 4K USB-C Transmitter	7488000365	295,-
Klick&Show 4K HDMI Transmitter	7488000364	295,-
Kindermann Soundbar 2.1	8715000300	99,-
Kindermann Soundbar Elite	8715000600	249,-
Kindermann DisplayLift rolling stand	4013000401	995,-
Kindermann Sprinter DS	4004000200	525,-
Kindermann Displaymount M	7550000003	29,-
Kindermann Displaymount XL	7550000001	43,-
Kindermann OPS PC i5-12450H	3051000062	895,-
Kindermann Android OPS	3051000100	450,-

*All prices are net, plus VAT in euros. Subject to change and errors. Our general sales and delivery terms apply. Changes reserved in the interest of progress. Images and technical specifications may include optional extras and are non-binding for execution. All measurements are subject to standard tolerances.

Presented by:



Kindermann GmbH

Mainparkring 3 | 97246 Eibelstadt | Germany

Tel. +49 9303 9840-0 | Fax +49 9303 9840-101

www.kindermann.com

