## Key **Features**

- Advanced ergonomics with a 40° tilt, 130mm height adjustment,  $\pm 60^\circ$ swivel, and  $\pm 90^\circ$ pivot
- Flexible connectivity with DisplayPort, HDMI, VGA, and USB 3.2
- TCO & Energy Star certificated
- Versatile stand design for mounting a mini-PC or cloud client



## Product **Description**

ViewSonic VG2448a-2 is a 24" Full HD monitor with productivity-enhancing features including IPS technology and an advanced ergonomic design for the modern-day office. Utilizing SuperClear® IPS panel technology and 1080P resolution, VG2448a-2 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customizable adjustments currently available to provide maximum comfort, including pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448a-2 uses environmentally friendly packaging and offers a quick and easy out-of-the-box set-up via the quick release stand. The cloud client mounts on the back of the monitor stand coupled with cable management design features make VG2448a-2 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.2 inputs.



Visit Us

www.viewsonic.com

DISPLAY		VIDEO INPUT	
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -
Viewable Area (in.):	23.8	3 ,	DisplayPort (v1.2)
Panel Type:	IPS Technology	Analog Sync:	Separate/Composite/SOG - RGB Analog
Resolution:	1920 x 1080	ERGONOMICS	
Resolution Type:	FHD (Full HD)	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	50M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	250 cd/m² (typ)	WEIGHT (IMPERIAL)	
Colors:	16.7M	Net (lbs):	13
Color Space Support:	8 bit (6 bit + A-FRC)	Net Without Stand (lbs):	7.1
Aspect Ratio:	16:9	Gross (lbs):	18.1
Response Time (Typical GTG):	5ms	WEIGHT (METRIC)	
Response Time (GTG w/OD):	5ms	Net (kg):	5.9
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (kg):	3.2
Backlight Life (Hours):	30000 Hrs (Min)	Gross (kg):	8.2
Curvature:	Flat	DIMENSIONS (IMPERIAL) (W	XHXD)
	60	Packaging (in.):	23.4 x 15.6 x 8.3
Refresh Rate (Hz):		Physical (in.):	21.2 x 15.99~20.15 x 8
Blue Light Filter:	Yes	Physical Without Stand (in.):	21.2 x 12.6 x 2
Flicker-Free:	Yes	DIMENSIONS (METRIC) (WXI	HXD)
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)	Packaging (mm):	595 x 396 x 210
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Physical (mm):	539 x 406.19~511.9 x 202
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	539 x 320 x 52
COMPATIBILITY		GENERAL	
PC Resolution (max):	1920×1080	cTUVus, FCC-B, ICES003, Energy	
Mac® Resolution (max):	1920x1080	Regulations:	Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, UKCA
PC Operating System:	Windows 10/11 certified; macOS tested		
Mac® Resolution (min):	1920×1080	DACKAGE CONTENTS:	VG2448A-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
CONNECTOR		PACKAGE CONTENTS:	
VGA:	1		Please dispose of in accordance with
USB 3.2 Type A Down Stream:	4	Recycle/Disposal:	local, state or federal laws.
USB 3.2 Type B Up Stream:	1	Warranty:	*Warranty offered may differ from market to market
HDMI 1.4:	1	Power Management:	Energy Star standards, EPEAT
DisplayPort:	1	Tower Management.	Energy Star Standards, Er EAT
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	12.2W		
Eco Mode (optimized):	14.13W		
Consumption (typical):	16.6W		
Consumption (max):	20W		
Voltage:	AC 100-240V		
Stand-by:	0.5W	•	
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE	,,,,		
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu	_	
OPERATING CONDITIONS	gj, 00/0p monu		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL			
Fraguescy Harizantal	24 - 9284-		

24 ~ 82KHz

50 ~ 75Hz

Frequency Horizontal: Frequency Vertical: