

APC NetShelter Rack PDU Advanced, Metered, 7.4kW, 1Phase, 230V, 32A, 332P6, 40 Outlets

APDU10150ME

Overview

Lead Time

Main

Colour	Black
Product Or Component Type	PDU
Pdu Type	Metered
Cable Length	3.0 m

Complementary

Main Input Voltage	230 V 1 phase
Height	149.0 cm
Width	5.6 cm
Main Output Voltage	230 V
Depth	7.5 cm
Net Weight	6.2 kg
Mounting Location	Side
Mounting Preference	No preference
Input Connection Type	IEC 60309 32 A 2P + PE
Mounting Mode	Rack-mounted
Number Of Rack Unit	0U
Mounting Position	Vertical
Communication Port Protocol	1000BASE-T 10/100BASE-T
[In] Rated Current	32 A
Permissible Voltage	200240 V
Input Current Limits	32 A
Load Capacity	7400 VA
Network Frequency	50/60 Hz
Number Of Power Socket Outlets	20 C13/C15/C19/C21 20C13/C15

Environment

Product Certifications	TAA compliance UKCA
Standards	CE EN 62368-1
Ambient Air Temperature For Operation	-560 °C
Relative Humidity	595 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	595 %
Storage Altitude	0.00 15240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	8.2 kg

Logistical informations

Country Of Origin

Contractual warranty

Warranty 3 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Regulation	REACh Declaration
Rohs Exemption Information	Yes
Mercury Free	
Reach Free Of Svhc	