


## LED floor lamp MAULjura, dimmable







- Stepless dimmer to adapt to the tasks and personal needs
- · Powerful direct light for the work surface and indirect light for room lighting
- Professional floor lamp for the price-conscious
- Upward light dispersion 50 % and downward light dispersion 50 %
- · Very economical: State of the art LED technology
- Designed by MAUL: Developed and constructed in Germany
- · GS label for checked safety, technical safety concept Made by MAUL
- Column and head made of high-quality aluminium
- · Closed lamp head
- · Convenient: Diffuser for reduction of shades
- · Guaranteed: No consumption in switch-off mode
- · Light source and operating device replaceable by an electrician
- Recyclable packaging
- Available from 07 / 2024

Illuminance of the: 1.960 lux illuminance at 85 cm distance, 1.220 lux illuminance at 110 cm

distance

Colour temperature per light source: 4.000 Kelvin (neutral white)

Number of light sources:

Energy efficiency class per light source: D (spectrum A to G)

Weighted energy consumption per light source: 62 kWh/1000 h (2 x 16 kWh/1000 h & 5 x 6 kWh/1000 h)

Service life L70B50 per light source: 50.000 h

Useful luminous flux per light source: 9.200 Lumen (2 x 2.500 Lumen & 5 x 840 Lumen)

Base: base

Material: Head: Aluminium - Column: Aluminium

Dimensions: Height: 195 cm - Head: 65.3 x 25.9 x 3.5 cm - Base: 41 x 27 cm

Movement: Head: fixed - Arm: fixed

• Guarantee: 2 years

| Art. No. | Colour | EAN-Code      | Tariff-No. | Cable length (approx.) | Protection class   | Pack size / PU   | Weight  | PU       |
|----------|--------|---------------|------------|------------------------|--------------------|------------------|---------|----------|
| 8257102  | white  | 4002390091435 | 94052190   | 2.50 m                 | I shock-proof plug | 120 x 50 x 12 cm | 15.1 kg | 1 pc(s). |
| 8257195  | silver | 4002390091428 | 94052190   | 2.50 m                 | I shock-proof plug | 120 x 50 x 12 cm | 15.1 kg | 1 pc(s). |