

# Reliable Printing Exceeding Expectations

Designed for the high volume user the ECOSYS P3155dn is perfect for sharing in large workgroups. This high productivity tool will sit on your desktop and power through heavy workloads delivering the first printed page in just 4.5 seconds with the rest following at an impressive 55 pages per minute. Equipped with advanced power management, a 25,000 page toner and long life image drum the ECOSYS P3155dn will deliver maximum uptime and minimum running costs.



# **Specifications**

## **GENERAL**

KYOCERA ECOSYS Laser Monochrome Printer **Operation panel:** 5 line LCD/LED display with back light with alphanumeric keypad

Engine speed (pages per minute): Up to 55 pages A4

in b/w. Duplex print speed: up to 39 page per minute A4 Resolution: 1,200  $\times$  1,200 dpi

**Warm-up time:** Approx. 25 seconds or less from power on. **Time to first page:** Approx. 4.5 sec. or less.

CPU: ARM Cortex-A9 Dual core 1.2GHz (+ ARM Cortex-M3 100MHz)

Memory: Standard 512 MB RAM, max. 2,560 MB RAM Standard interfaces: USB 2.0 (Hi-Speed USB), 2 x USB Host Interfaces, Ethernet (10/100/1000Base), Slot for optional internal print server or SSD hard disc, Slot for optional SD / SDHC Card.

Integrated accounting: 100 department codes Dimensions (W x D x H) - 380 mm  $\times$  410 mm  $\times$  320 mm, 388 mm  $\times$  410 mm  $\times$  343 mm incl. projections.

Weight: Main unit approx. 16.0 kg. Approx. 16.6kg (with starter toner) Power source: AC 220 V ~ 240 V, 50/60 Hz Power consumption

Print - mode: 675 Wh Ready mode: 11 Wh Sleep mode: 0.5 Wh

Noise (sound pressure level ISO 7779/

measurement distance of 1 meter) Stand by mode: No measurable noise

Printing: 55.8 dB(A) LpA. Quiet mode: 51.1 dB (A) LpA Sleep mode: No measurable noise

Safety standards: GS, TÜV, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatibility. \*in a standard office environment

# PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray: MP tray: 60 - 220g/m², A4, A5, A6, Letter, Legal, Custom (70 x 140 - 216 x 356 mm), Banner paper up to 915 mm 500-sheet universal paper cassette: 60 - 120g/m² A4, A6, Letter, Legal, Custom (105 x 148 - 216 x 356 mm) Max. input capacity incl. options: 2,600 sheets Duplex functionality as standard: A4, A5, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm), 60 - 120g/m<sup>2</sup> Output capacity: 500-sheet- face-down with paper full sensor, 250-sheets-face-up with PT-320.

## **PRINT FUNCTIONS**

Controller language: PRESCRIBE

Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print, TIFF/JPEG Direct Print Support, Open XPS, Line Printer, IBM Proprinter X24E, Epson LQ-850 with automatic emulation sensing. Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL6/KPDL 3), 8 fonts (Windows), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417) Print features: PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, Encrypted PDF Direct Print.

Mobile printing support: KYOCERA Mobile Print app for iOS and Android; Mopria, Google Cloud Print, Airprint, Direct Wi-Fi (opt).

# **CONSUMABLES**

Average continuous toner yield in accordance with ISO/IEC 19752. Starter toner is 10,000 pages, A4. TK-3190 Toner Kit: Microfine toner for 25,000 pages, A4.

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets,

60 - 120 g/m<sup>2</sup>; A4, A5, B5, Letter, Legal, Custom

(92 x 162 mm - 216 x 356 mm)

PF-3100 Bulk paper feeder and PB-325 Printer base: Max.
2,000 sheets, 60 - 220 g/m²; 76 x 148 - 216 x 305 mm,not to be combined with PF-320

CB-360W Cabinet: Wooden desk with storage capacity, Approx. 380 x 411 x 508 mm (WxDxH) CB-365W Cabinet: Wooden desk with storage capacity, Approx. 380 x 411 x 254 mm (WxDxH) PT-320 Paper tray: 250-sheet-face-up output tray Caster unit CA-3100

Memory upgrade: MD3-1024, MDDR3-2G, DDR3, 1GB/2GB Storage Devices: HD-6 SSD hard disk: 32GB for easy document management. HD-7 SSD hard disk: 128 GB for easy document management.

#### **SECURITY**

Data security kit (E): Encrypts data stored on optional SSD, available when HD-6/7 is installed without any license UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available Optional interface: IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45). IB-51: Wireless LAN (802.11b/g/n).

IB-36: Wireless LAN (802.11b/g/n) with Wi-Fi Direct.

IB-32B: IEEE1284 interface.

#### WARRANTY

1-year warranty as standard \*\*. Kyocera guarantees the drum and developer for 3 years or 500,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

# **KYOlife**

Up to 5-year on-site warranty extensions available for product and options.

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership. The cartridge-free system means that you only need to add toner regularly. The modular design concept allows workflow enhancing functions. Integrated system software also provides crossnetwork compatibility.













**KYOCERA Document Solutions Partner** 

MAY2019DSECOSYSP3155DN/VER1.0

**KYOCERA Document Solutions UK** Eldon Court, 75-77 London Road, Reading, Berkshire. RG1 5BS Tel +44 (0) 118 931 1500 - Fax +44 (0) 118 931 1108

