



## 3m USB 2.0 Type C to Micro-B Cable, Anthra Line

Part No.: 36893

### Description

- Professional choice USB 2.0 Type C to Micro-B cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts
- Double shielded cable, corrosion resistant tinned copper conductors
- 10 year warranty

The Anthra Line USB 2.0 Type C to Micro-B cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

They are premium connections that feature double shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 2.0 Type C to Micro-B cables are available in the following lengths: 0.5m, 1m, 2m and 3m.

### Technical details

#### Connectors

- Connector A: USB 2.0 Type C Male
- Connector B: USB 2.0 Type Micro-B Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction:
  - C: High conductivity copper
  - Micro-B: Brass
- Pin Plating: Gold
- Dimensions (approx.) WxDxH:
  - C: 10.9x28.3x7.2mm (0.43x1.11x0.28in)
  - Micro-B: 10.7x30x7.6mm (0.42x1.18x0.3in)

#### Cable Construction

- Length: 3m (9.84ft)
- Standard: USB 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 3.5mm (0.14in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge Power: 28AWG
- Conductor Gauge Data: 28AWG
- Shielding: Aluminium Magnesium Braid 82%
- Shielding in connector head shell: Copper foil

#### Specifications

- Supported Bandwidth: 480Mbps
- Maximum Resolution: -
- Nominal Attenuation: 1-400MHz < 5.8dB
- Minimum Bend Radius: 25mm (0.98in)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: 0°C - 70°C (32°F - 158°F)

#### Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, California Proposition 65, UL

#### Purchasing Information

- No.: 36893
- EAN: 4002888368933

This product is also available in other lengths

- 36890 - 0.5m (1.64ft)
- 36891 - 1m (3.28ft)
- 36892 - 2m (6.56ft)
- 36893 - 3m (9.84ft)